I'm not robot
reCAPTCHA
Continue

Engineers black book download

>.;. / Common Conversnon Conversion Fuciors Fuclors 'V iE " \,, ;'V}"* _ / _ A 1 UWOIQWH" "W" ___ V ~'~ f - Ė M ~...._..... .-W»-V ENGINEERST ENGINEERS _.|_ 3,_ H V $0i?43P 1243? ' 'z .... ,_,...,.... .....-.-.-.. zr . `__ --_ , - 'L -< - __ 9 -=i "7 ~ x ; ""% __ ' 'vi?' Pä .=.\ ,.; _ ..!I-`z1 *._„z,f{1__„ —-0 - — # -12 *an ¡ fir?" "1-§ ~ ,Q -:Ä _gl ~.\ éa? flrazm =-:===- V L' -` -E 2~° EDITION Enmon 2"" ¡ llala Formulae llala Sheels $|lBBl$ II E0l'llllll|ńB 1 1 ||B|l!!0||'5fl Tfl|1|BS Tfl||1|B$ I Ellllll\|€l|BIII Ělllll¡\|ãl|!!ll| c|IfIl'lS fl|liIl'lS1 BBIBIBHBB \Ž \ ,- .. " ' _A ^Y Š 1o.6ss0P O 6836? "W" ' kg; _.._ . 1. IVIETRIC 'IO IMPERIAL \ z \ I _\.-. For defculed defailed Converslon Conversion Factors, Facfors, refer pages 4 & 5 BEN ~ _Ji—* E6 ikfl% E'? l _u1 Ží E E E ___1 _-II[5] |: E'$?;I|= 1 ""'"*?*"'"P!"'"'"'?' ~..] I O!U"! "*1; -12 if 1,„zz-e;n?|'1' I ' Tir 0 N O- *0;U1:00: Drmhari 0_.: 5 5: c:_ ~ _. JU '~~\ .P -. "'\ _/ „-Ąfl i*L _ i comp//ea by p .~ ~ ~ ... ' ... ' ... '

a- 1/2020151 1/2 ‘E ‘áizEu I"l'lan I3 In inin Use : Mechanical industry for motion Use : Mechanical industry for motion transmission screws when the load transmission screws when the load is acting from one direction, is acting from one direction, milis, etc. eto. e.g., in presses, rolling mills, e.g., in presses, rolling milis, mills etc 0.075P U.O75P I 2: c: -4.~| P , P i.O1.€~ ™- ix 0.5515P _L II _ I P P \| I to 60° \1/ Ĺ" lkjd . 0.1723P O.1723P _ \ i 1 Äln eotr gofi 60° 600 055921-I O5tI92P SD ‘U I/ axis ms of Screw iHlfiil il ftil ilflilfl I -il-l131>>'U'U I'rriZu I"'I :io -L o.4579P 873° Å XT I 90 Q 0.1520P U152UP_4 - eotr _ - 1.65 4$.15 .Q ‘U T eotrL P90.. 90° ’ TAPER 11:56 ífip 0 ’ 06p axis of screw (V-0.040” FLAT) API : TAPER 1:4 Q!)-0.040” : TAPER_1:6 (V-0.038”R) API :TAPER 1:5 (V O O38”R] Use : Oil Industry Use: Oil uii industry T - El Å common FORMS GDMMDN THREAD THREAD FDRMS usen IN IN THE THE ENGINEERING ENGINEERING INDUSTRY USED INDUSTRY i. EAD FORMS FDRMS COMMON THREAD :I C: U! ii-: : :I:Š ru ENGINEERING ËI = E! 5:':3 USED IN INDUSTRY ii THE c:varu:I 2 e» šsl S side,., J B(Np,) B(NR) I I 0.626PP 0.e2e0i= 90 0% .`1 axis of screw Il Il f Ñ! Ht{—l_—4 B(ER) B(EFl) imvi 90° _ . lflill *1"/47' Ilii E `1 O 3,, \ I O.'|i98P 0 .1 19BP 1116 TAPER 1:16 TH I Use : Oil industry 0 e605P aw 0,15%: O.1fil'l1P P 01373P 0.i373P Tj A _I _ i` 0 1 vi i .i,. I s QM” l rAPER1;e 0i1501P TAPER 1:80 l-l60iP BOLT 90-1 0.1373P of screw ~axis 51 BUTTRESS API BUITRESS Use : Oil industry for casing Pipe size : 4 1/2” 1/2” to 13-3/8” 13-3/8” 01601P 0_16[}‘iP l a ™ -"1™ \vri in tn} il T \¥ V o1a73P O.i373P l I'-Ĺ L BOT O 16I01P 01601;, BSP (G scares) seniias) B-SP M axis of screw API : TAPER 1:16 (ROIINDED) IRDUNDEDI A l nut ~ - \ rpi -\ l—-35.’ 0.1a7aP 0-1373P 0.1 19ЄP 0.1198P BS GAS [BRITISH STANDARD STAND (BRITISH (BRITISH {BRITISH STANDARD GAS) Use : Valves for gas cylinders and similar pressure vessels PIPE PARALLEL) PARA I Use : Fittings and pipe couplings for for gas, water and sewer lines l i i NUT It - \ B(NR) B(ER) Blue) B(ERl 1 2C >2a' ‘rÊ¡i'Q.. 2'2°23' |3Q|_'|' ž :OLT i 10 90 l P -i-J (yąggp O.i808P S I 5_ i V \ 1) 1.1`363P l.i|363P i i 4 ¡1 Q_6p g_(5[:> 47 59 47.5,, , i siiwet Parallel to taper Paralleltotaper O axis of screw 0.1808P U.) BUBP BOLT -_\ £l.9602P 1%; 1 0.2682P 0.2ea2P L I T* I 3 -W W' .5' 51,’-ci OJ 1:1 0.1373P fl1fifl'1P 0.16 /'-1. t___ ljm VĹK i O 1 0.se05P 1 .iu 0.9605P cncri I gp O0.600 I. 640 3P 0.I373P ..0 3 E’ OJ -U1 H c La. “UCD cn Cn-i:i Ī OKSBOP o.0seoP I Im? ——I- -—- 016 P 0.1601 B_$B jBRITISH |BRITISH STANDARD TPII BRASS - 26 TPI) ngs Use : Brass fittings tidings and pipe coupli couplings é I .I . , 0.6403P ~ 1 1 1 14 “W l 7___ - I 0.i6OCP I 90° I 013773’) SP 0.1000 TAPER1I16_* TAPER 1116 A ' 0137 BSPT (Re (Rc szniis) SERIES) Ĺ (BRITISH sro. TAPER) STD. PIPE TAPER) Use : Pipe thread for steam, gas and water lines F Fit . iI P c cn -1:: o.1eesP H '..» 0.8$57P Aki O.53?'/P io; I 1: 053070 A AT BOLT OU p iih in n2 iiz męęsp Ili ül flilflilfl flflli 0.941 0.ee2 0.002 does 0.000 0.042 0.040 S;Š l f[1.411 1.046 1.040 e.10e 0.100 0.0ee 0.000 » O//7’T one/V axis of screw MP 0.i6eeP BSO! }BRITISH STANDARD CYGLEI (BRITISH CYCLE) Use : Bicycle industry y A -. H \/lLLi_' i(oiesev O1601P QJGOTP Z CA3 —_|"UCO “U 01373P 09605P 0.9605P \/ ti f' axis of screw screw EBr—-— L 1- . X ‘\. U3 Q BOLT P 0.1seei= CI —-I il arm ' BOLT 0263? Use : Fine - mechanical industry utllity, electronics. especially electrical utility, P 1 ~ : >| 0-1591'" 01500' U.2682P Y -UT Z (I '-I I1 \Å / >' Nut ýy _ A T p I 55,, I P o.e40sP O.l373P B.I-I. I17 I 0.1e0oP o.1e00P t 1 (BRITISH ASSOCIATION) ASSOGIATIUNI (BRITISH BU1TRESS API BUTTRESS Use : Oil industry for casing Pipe size : 16” 16” and larger P 1 i TAPER 1;ie rAi>Ei= BSINZ BSF BSW [BRITISH STD BSW IBRITISH $TłJ- WHITWD WHITWBBTHI| BSF (BRITISH STD STD. FINE)I Use : As a general machine thread tlse na 00.052P 052P O0.052P 052P P T 27 Z (I —I . ‘IV I ~I ,L EL-:I-I -uI~—:r 1.814 2.200 a.17s 3.175 1.014 2.209 1.396 1.692 2.442 1.300 1.092 0.109 0:32 0.175 ears 0.100 0.132 0.060 0.089 0,132 0.132 0.000 0.009 DRYSEAL Use : Widely used for fluid-tight pipe couplings in the motor industry coupiings 1 L 0 864 /š -»I 9°” I 0.351» T 01050 0.105r» , so”) TAPER 110 U axis oi screw I HUGHES HH-90 90 llse : Oiiiiiiüusiiy Oil industry use I 7 ~. 1&1 ëfl HREAD FORMS FDRMS GOMMDN T common THREAD EERING INDUSTRY USED IN T"E.E["i"E.EB"""I".""$T"Y THE ENGIN "SEN" PP . ‘T . _"—’d.125i=i n19i:i= '"' \ _ U.TEUZI" 0,108 ZF ‘W' P k O.iOB1P 0.10e1P i O. i _ . m 600 . 0.0722P)I 0O of6134 34PP I 0.8657P I (§) - l of"! .^~' IT) °""'43P [)_25P 0_25p ih’ 0.6495P 5P _ I / eotr BOLT 0.144-3P 0.1443P I M [ISO METRIC) METRIGI nso ~ V $ di 0% P O“WP O38P _ 0.8`G60P O.8|66OP é < i J_ 0.0330 CD CD Ci.) CO TU -U i 0.0_057P I 0-8I657P ) BOLT oeeeeoe 0.66660P 1TEIBEOP .s000P i< 56° t 58... U . I 90° so” ‘{1 ' /\ K. 30°O .--” J>`U :i==”U C0 CD -._->»- OF3_O(J1U1 ‘U ‘U I ‘-4. 3> j> -><-4-] >-4- ->-> axis of ot screw $0.65-33OP 10.683OP ~- CIT CD - _L |\J >i2mm 12mm -v.Omm 1.0mm BonBOLT pmNo.OLI gml\Ji mcn (II .C’Um: 01 (TRAPEZ) ITRAPEZI DIN 103 Use: Mechanical industry Tnudtery for motion transmisson transmission screws STRAIGHT THREAD] THREAD) Use : Mechanical couplings of tight tubings normally not fluidfluid-tight tunings ‘I I ‘° + 0.s0;seP U.5959P "'I. OI” III H 80., 80. t _ 5 I T’ iI o.e000P oeeeoe I S ÉA I ' - 0.4;erP 0_4Ž07P BOLT uz D i1 01-mâe _ o.1oe2P D.1082P U.i443P I i I" -Š 0.25P o.2sr> —"'| I) 0.7222P O.6*134P 0,0ü1a4P) `\/ ‘I Wt I 0J082P o.1os2P .--i-— Ñ """" 0.25P 0.l443P Flat or Rounded C.25P O.i443P I-IE E IUNIFIED NATIONAL FINE) (UNIFIED Use : Mechanical industry i o.1oe2P O.i082P y _ I _I 9%— —-—-'-l a ,k (MSP i _-FIBI ‘ 0.0722P o.0722P Ii I(0.6i34P o.01a4P 0-86501’ 0-BÕGUP 1 i ,I "'1_§i,_ _ _ Flat or Rounded 013 r\: can "U [La OEŽP II qr ‘Níllfí :_ I IINII LINC IUNIFIED NATIONAL GOARSEI [UNIFIED COARSE) E B %i=fi ——P—-m25P 0.120P W, use Ii o.ae|e0P 0.00\00i> l '- iI TAPER 1:10 0-0328'" 0-0328 P \ |TAPERi:l6 7 ' ,4’ I Å ii/_"\Vl I I I I I BOLT 1 IOa O E :=- :| 30° :: 513 CI'l -J cu DIN -i:|: *\l -1——a- ll'l {VD 0.osiei= 0.0328 P O.683OP PI 'U"U T [NATIONAL (NATIONAL PIPE Plpe couplings where there is Use : Pipe no demand for fluid-tightness ,1 _ 1 O.i243P 0.124sP fi P "PI I .essoe I gqn 0.1P II I: ‘U ‘U Ell 4. #_ U3’ . 1: 'I. '__»2Q-i 'U \___.. RD DIN 405 an _ I Bon U"! I BOLT eotr U.'IU8iP 0.I081P TAPER 1:16 IAPIZRTIIB _ P0caco-Ucio ‘U % T c:o.2aasP I I 0525,, o.s2.%1.P \[_°_ i|\,o.eseP \ ifilâflp l igrilrtt 1 0.117sP"(+4I 3 J 0,750 , /\Iy ((0.45(0i= l orsr>ir I km: 27 >~4- 1 i ‘i I V»~ cn l METRIG TAPER M Use : Grease fittings and pipe couplings Use : All branches of mechanical industry C: —I .. il I 1 4 AH; 90, 90° 0 -1082p 0.10B2P : ' axis of screw _ i ^0.2211P 0.osi> 06830,, 1 QYÅÑF *iii* \/ (Q Š OP ¡_i_, i—-—P—~t . l lÉ_I-: EI i oi, t._R_.-: E 1 CU i Ę 1 i——P€~i ll ! IR H COMMON THREAD .,__ P.9Ĺ'lI'II: !I'1°_ *I.IÉ' .F_E! = ::::IFORMS 2Ë EE :iw::vi_ : USED ENGINEERING INDUSTRY U$I:I.I IN THE I:NiIlNhh EI , iIi I 0.1443P o.144aP *Root Radius ROUNDI (UNIFIED NATIONAL ROUND) ` UNR _ IUNIFIED _ Unihed .. National . Round (round root) * UNR - Unified t I ' W 0.1oe2P 0.i082P y I 1’ o.09o2P 0.09ozP 10.5774P i0.srr4P _ \/I I\/ I I_ku_(M_ eotr ' '_'.— I(,_ I I °iI8°4P (11591 Pp 01501 *R°°III*"'"S *R°°m*"'"S "ml „.eN.:.Be¡ ¡ :Đ EE : ąnnl' u: : -[I _AB uIE 5 II I I C C 1all >1- 1.:: :: G- _ T5 Ac: :: -|-uIlillnl-I-IJ applies to External Threads. ItIt is a UN thread in aII "'"' 'II\I\|I "V _ ""' External Threads. Root Radius ma :1 =r::._.- PiD æe:O"EQ "0 plies to respects except that the root radius must be be rounded. rounded 3>APPIÊS TO Ëb>íÎfpina||ThreładlíÍ\ãcI>ott Radiuls rnãn Å '1 BOLT|-/ B(]|_'|"|_/ I _' E (NATIONAL PIPE TAPER) Use : Fittings and pipe couplings for delivery of coolant to the cutting edge. Spiral / Gun Point lil >x< I efil Straight Flute Ta Tap sirai iiieiuie mainly tortapping through holes. The point the chips The spiral point tap is used malnlyfortapping poirit helps to cut cutthe of the tap, leaving the flutes clear forthe free with a shearing action directing them ahead oi’ to the point. flow of coolant coolantto iiiiiiiiiiieui Flulnlnee Flnfnlnee . .....,,... Tan ...E ‘1 without Oil Grooves without oii empires WQZE. .41 $1 I I I I I 3 .Il >X oil grooves helping to deliver lubricant easierto thetap point. Taper Plpe Pipe Straight Flute Tap . - r Q E Cut — Threa i1re ' :ąú_ r"-1' ";:I.f. tn, -:_ . '.', v i , '-A Chamier Chamlef Lead A ' 115€* . Heat Resistant Alloys r~ il IiIiIIiiIiIi IiIl se se M &×s.s\sw I1 A f "ff` Orange Ullite Š. I . = En rm I n r| 'Ferming """'"5 Lead I Free-cutting Steels, Steels S . . ' Structural Steels, teels, Aluminium, Copper, Therm0p|aSt¡cs' hermo plastics. i i 3 1200 N/mm‘? 2 -.__i CE __| - 4|(\.f\f\ |i|r_ DLUUIS 3 ldUU l\IfIIiiIl Stainless Steels -lr_Cš 5S 1000 iv/rrrrrr N/rnmz r 5 - 15 m/min. .i . 15 in/’iiiiri. m/min. 22 -- 15 15 - 30 m/min. Grey Cast iron, Iron, Malleable Cast . iron, S. G. iron, Brass 8.& Bronze. T5 _ 15 _ ' 30 m/mm' m/min’ Alloys ' Nickel-based Alloys, II I . Cobalt-based Alloys, Super Alloys , with Hardness < 350 HB. . 3 - S m/min. Structural Steels, Steels. „.__.__ g. „M oieeis izuo iv/inin z Alloy Anoy Steels, SmehSteels. Carbon Steels,' n1- 15 -» SO 30 m/min. I\Ii’rrirIInrr Q. Pac-13 I-I rI nnrI C’-I-nnln IIILIILITEIH IA UUOU lI QB ‘-1C Q) DU ULUUID. ,1 Cast Irons » Oi Gii| wik Grooves Ir . /< _ L _ Fglprmeg ormed . rea Tiireaii_¡z I f' | 1H I n n \ T __=I" (Setting) . i; Zi. Auuumw 1-jf; ;;;Ž'¡~' ¡._i. II"'"; Tl}_5 . \ \I Ir ? Tapping Speeds ggggIgdh in/miri. (Coated) Steels ' Heat Free-Cutting Steels, Treatable Steels, S. G. Iron, Nitriding & Case Hardened Steels. @ ieesoiv/mrrr S 850 N/mmz Ittliite .Vl'1'1'.i° . TAP GEOMETRY Fintaies ĚutelessT_`__~ _____ WW Material (Examples) Examples rice iiiduhiiiiiig, iriiauiiiiiiiig, Austenitic, /~\u_5l€l11lIlC, . Universal U . IAApplications1 . . SQIAEIIÉ1 1(_Steels 51000 N/mmi " Green UTUBII Pipe Plpe taps are designed primarily for threading pipe fittings and are suitable for hand and machine use. Pressure Points Martensitic Stainless], Ferritic & Martensitlc ýý 4 Steels. I'\.'_ Thread Cuttino Catrina - _-.... _ Ta 3 i1 "PF /7; "L A< ,.;;; ?'-Ť"*>"%/~:~. _ Steels, Steels ' High-Speed I-it atA H d, Sh Ch . . I Hard, Short,t, Chipping , Tool ,,M, Steels ,_,,,_'___, ,,,__,_ Steels, Q Case Hardened OLUUIIS, Steels, I"IUi.1l Heat ' ' N uclbG'llc1lUUIlUU mjledn Q MME:1ąer¡a¡s0Ĺ120'(?Iü?r%m2 at eria- 1 s _< /mm 2 1 Treatabl ` Treatablee Steels. Ste eis . e The application oi the treatable steels of the fluteless ofthe fluteless tap fluteless tap, with the Flutes , T Staimess steels St I w t it gfl iiiiiiiiiiiiiiiiiiiiiiii.-_Š '1'I'I'lll'llllllllllll 1'\'I'I'\'\'lllllllillll 1 p 1 b I in. © gsofuon Soft Long Cm Chipping - S Bgghfimma Yellow ; Materiamgg Materials 800 N/mm z A 4) , L f"\-....-._ _J-~l-,-.-'nip-4.-r. A.-III l'lT"'IfI\'I 1'\Y'f\ r\rl||r\||I r in-I-v+n»-1+ Fluteless FIUIBIBSS Tap Tai! with Oil Grooves I I 20) 0.2682P 0.238213 I I To find Iind Tapping Drill Size for MB M6 x 1.0 1 .0 tap with 70% thread Example : T0 70 Xx 1.0 Drill Size = oriiisizz = 6.0 0.0--— 76.98 \ Nne ii Z Š :1 31 i _ i m' ię METRIC INcI'I INCH 11?. lw TAPPING 5"'HPIN DRILL SIZE FOR 'I'l Cl :I THREAD -i:I :I Elfl:I UCUTTING I- Z:ili mi= TAPS l'I'l-I=| 'II UI 61)2 c: -[P,:I CALCULATION GALCULATIUN OF TAPPING DRILL FORMULAE I FURMULAE FOR THREÃD OUTTING TÂPS F0" TAPS 1 O.2682P å-I_(anirisri ASSOCIATION) iissociiiriiori) (BRITISH IQ _- I D-Hr. = .2010 .2010inches inches = 5.1 mm I(Basic (I Basic Basic ' Basic Tapping ICIearance Clearance ITapping 1 Drill ' Drill I(of of Thread? Size Size L Thread Diameter i Diameter 5 Diameter ;(inch)] (inch) _ (inch) (mm) . i"'"'I (mm) (inch) (inch)-I (inch) I (inch) (trim) P¡tch`I Depth Iilepth .i Ngular Iiflective Mayor Minor I Q en ' Pneii ' leneeriirei FOR eagles-.eş.§ FLUTELESS TÂPS FUR [email protected]> METRIC __ MaiorDia. Th re ad Drill Size = Basic Major Dia. of Thread- ` % ‘E/0 of Full Thread x Pitch (mm) 147.06 147.06 Ilo. I 0.2126 0.2120, _ 0.2087 0.1874 0.2007 0.1074 .0319 ` 0.1850 0.1659 .0010 0.1000 1 3 I.0287 .0287 I 0.0172 0.1614 0.1441 0.1014 4 I .0260 0.0156 0.1417 0.1417 0.1262 . D s5 .02a2 0.0139 0.013; 0.1200 70.1120 .0232 0.1120 0 0.0125 0.1102 0.1102 0.0970 ..o2o9 0.0125 0.0070 0159 0.0113 7 I .01e0I 0.0110 .I 0.0904 0.0004 0.0070 0.00703 .0169 0.0102 0.0866 0.0764 0 I .0 010 0.0102 0.0000 0.0704 0.0092 0.0748 0.0656 0 I .O154 .0154’ 0.0002 0.0740 0.0050 I 10 I .0138 0.0669 0.0587 . 0100 0.0083 I 0.0000 0.0007 5 7 11 4.0122, 0122 0.0070 0.0073 0.0591 0.0591 0.0513 0.0010 I 121 5 0.0066 0.0000 0.0512 0.0445 0.0445 I 10I . 0.0000 0.0472 0.0059 0.0413 0.0410 _a.e_a _a J:-e.-:|\ -Ac"° -' 0.0054 0.0394 `.oi:`o'oo-mu::- ->mo 0.0339 0.0000 15 I .0083 0.0305 0.0050 0.0354 0.0005 7 1eI 15 .0o75 oooš 0.0311 0.0311 0.0200 I .0075 0.0045 I 0 :Ā _ .0394 .0354 I` .0054 1 0. 0236 0.0236 1 0.2362 0.0213 0.0210 0.0191 0.0101 0.1890 0.1000 ëüülü-I 147.06 {I I = 5.5 mm INCH Dm' Size of Full Threadd . Thread - (0068 0.% °IF"'"I'"e" Basic Major Dia. of Thread— xmrea-šasfper inch) DrllSlz0 = 00010 .0000>% I Threads per inch) __-1 lind Tapping Drill Size for 1/4-20 lap with 75% thread Example : To find _i_ I Drill Size = .2000-I.0000> IIDTE : itlt is advisable to use a good cutting oil or lubricant rather than coolant for Ftuteiess Fluteless NDTE (Thread Forming) taps. Correcttapping drill sizes are equally important. I Il.Il lMII ltMli lM 14I E 2 I I ZZ Z—I Q9--L O02 ' 2 _ ZZ $3 COCO DO-I» 4. 5.10 0.10 . 0.1268 0.1106 I 0.0661 0.0001 1.80 1.00 1.55 51500 1.40 1.40 1.205 1.05 1.00 . 0.90 0.00 I 0.80 0.00 0.70 0.70 0.00 0.0504 0.0004 0.0445 0.0378 0.0070 0.0354 0.0004 0.0283 0.0200 0.0256 0.0200 0.0220 6.10 5.40 i 0.40 4.80 4.00 I 4.00 3.40 TIT 4.20 3.00 3.70 F'-"9" ca-=11: 0.70 2.05 3.00 2.55 0.00 0.0900* 0.0980 0.0550 0.0000 0.0750 0.0563 0.0000 I 4.50 4.00 0.1468 _ Example : To find Tapping Drill Size for M6 x 1.0 tap with 70% thread 70 ×1.0 6I0_70x1.0 ri Size ize = 6.0- 14706 D'lIS' Drill I 0.1661 0.1001 2.30 2.30 2.00 II I I' 2.90 I 2.00 2:60 2.25 1.95 1.75 as 1.00 1.60 I I I 1.40 140 - 1.30 1.10 0.98 , 0.00 I r \ Å' 7 7110011113 SIZE _ TAPPING mmu. DRILI. SIZE TAPS NG 7113540 0077103 ms THREÃD GUTTI FOR 0%' L"iP*"'" 0.13739 K 0.1373P 0 W 1 0.9005P 0.93053 1 550 1.- ’. 1.-A 1 X/ \/ | 0 1373P 0.1373P ' |-'BSU1! 15_W 301.7 1 \_ E 0.111010 0.1001P . 1 1.85 _; 2.50 0.0672 _H1.35 .0133 'R1' 0.0930 _' 0.0005 M3/32 4_3_ T0133 0.0933 0.0305 10.0372 2.50 I .3/_33__ _ 48 A 2 /U-14 n mvm n : _: 7 o 7' of on 7 L.\m a.uu 0.1.11.1 .0160 U. ILUU 1 0.1090 u.12auA u.1u:1u 10.0930 _ _ 1/3 .0130 2.55 1/0 _ 1 40 ,02Ĺ_ 0.1532 0.1562 _1 0.1362 _5/327*' 32_ 10200 0.1332 I 0.1162 _3.20 _ 4.10 _5/32 4.90 .0267 1 0.1875 .0237 0.137 5 1 0.1608 0.1303 0.1341 1 3.70 3/16 3/10 fi_ 24 0.1054 2 133 0 0.1921 .0267 zaN 1 N24-I> 7/32 .0237 0.0.2100 0.1354 1 4.50 1 5.70 Q' I'1'-190 Fi/7. 1/4 on ' ,vuzv nfion n oqnn '1 0.2100 n - 2139 5111 5 513 _J 5.10 6.50 , .1 20 1 "0.2500 ' 1 Q0.1000 "13513 1 8.10 0.50 _0 0.10 0.2769 0.2413 .0356 5/15 _ 0 18 13 .0353 1 0.3125 0.3125 0.2739 0.2413_ 3.50 5/10 9.70 0.2950' 1 7.90 .0400 70.3750 7 0.3750 ` 0.3350 0.2950 177773/3 7* _15 13 1_ 7-90 _ 9-70_ 3/Ĺj.. 9.30 ' 11.30 0.3910 _ 0.3431 0.3401 0.4375 1_ 0.3913 7/_1 6_ 11 14 *5 .045z__ 1 77/13 .0457 91.301 11.30 1 13.00 J. 0.4466 0 3932 1 10.50 _1i100 .0534 1 0.5000 _ ' 0.4433 0.3932 1/2 1 12 0.4557 1 12.10 14.50* 0.5091 9/10 9/137777777" _ 1 .0534 ' _ 0.5025 0.5325 0.5091 0.4557 14.50% 10.25 13.50 3 0.5000 1 0.5086 0.6250 1 0.5333 5/00 11 __ .0582 1 0.3250 775/37777 TW32 0.5033 1.50 13.25 17.75 A 15.00 0.5711_0.6293 .0582 0.6875 711/917377 11 .0532 0.3375 0.3293 0.5711 1 15.00 1 17.75 .11.1Ĺ1. Š 11 0.6220 1 10.25 _1 .0640 0.7500 3/4 1 10 .0340 0.7500 0.6860 0.3330 0.3220 13.25 = 19.25 10.00 21.00 0.6845 _0740 0751_1 0.3345 0.8125 __1_3/18* 10 Ž .0640 Y03125 1"'1':I/11'3f '1_ 10*".1i340 0.7435 22.50 0.7328 1 19.25 0.0039 0.7323 0711 0.3750 0.8750 7"?/3 .0711 0.3039 ÉÉ 99 24.00 _ . 64 _ l 0.7953 20.75 1 24.00 0.0004 0.7953 _ 20.75 0711 1 0.9375 A 086 15/15 11715/13"11 9 ".0711 25.75* 0.0400" 22.00 1 . 0 0 00 1 00.9200 0800 1 1.0000 1 .0300 . 9200 0.34001 25.75 _ 24.7? 29.00 1 .1 250 "1117 1 .0915 091571 ` 1.1250 1.0335 1 0.9420 1 24.75 AL 129.00 _1.1/É... 7 ,__.3 20.00 32.00 .0915 11.2500 1 53 5 1 11.0070 111/4 1/4 .0 9 15 . 2500 1.1.1505 1. 0670 23.00 1.1010 30.25 ` 35.50 35.50 fi _1 _.3750 1.2000 '5.1313' 1 1 3/8 1 A .1037 1.3750 1~ 1.2333 30.25111? 1067 30.50 0j 1.3 933 ` 1.2000 1067 1 11/2 1 Ā .1037 1.5000 1.3933 1.2333 1 33.50 33.50 33.50 41.50 1 35.50 2'u'r01"Ch\ic> ‘ ""1 1""*"' .0 T4939 . .000 * OELUU _7’ *1. 1.6250 1.4909 1 I .OU00 1201 1 :1/___3 A . Ji'/U 1.4938 A 39.00 . 45.00 1517500 1.4933 1.6219 mm oocx 1201 1.7500 ' 1.3219 5.010 1 3/4M _13E.. 41.50 _40.00 1.0750 00' .1 423 1.-0 7/3 41/2 .423 1.750 .0 1.7327 1.5904 77:10.50 ’ 43.00 \ na. 51.00 7 1.71 57 444.50 4.50 17.00 1.8577 1.7154 4 1/2 2 7 .1423 1 2.0000 1.8577 54 2__ 7 41/2 . /1 7"' . 1[2fi'| 0 ocnn 0bvvvv 11 . 0052' nv/T ii. «ÉH ‘J rmoo 05100 09 Rflfl 151.00 51.00 1 ' 50.00 92 .N .W . 7; 2.250? .,,, 64,00 57.00 34.00 1 2.3399 2.1798 1 57.00 2.5000 ; 2.3399 21/2 1 .1301 2.1793 I 21/2 4 .1001 lf'l'"' ' 1 LU_ .U\]L..u _ I U - L U UV 0 1/0.2. r 1 /I '1' . luul r_..c.uuu 1-. u u u u I - u L -Iv 4.- 1 + 0.1601P CD ' __I. CDCD _.1. "Ú -Basid Basic 1_ " :'Basi0-"Basic 1'1 Biasi-0 Basic .1Tappin \Tapping 015101 1511001 Mai.n'1* Efiect - Minor _1 D'lI fl Drill mnhii 1 I Diamclè Diamnfnr nlnrrnlnr Diarncier E2:0rceler nulnunn 11 Size (inch) (inch) ¡ (inch) inch) _ 1115311) 1111011111 3 (mm) (mm) I IIIU$U'I 0.1475 0.1475 1 4.00 0.1730 0.2008 _ .0534 _ . czO532 U:oo 2 0.7500 0.8750 1.0000 1.0000 _0.6966 0.6966 081681 0.8168 CD O2 'R1 1 1 1 1 101 1 } 2 2. . ' 21/4_MW 21/2 1 _,_ 1/2 _ ž 11 1/2" j : mnom 01.19/43f' 3/4 *_ O':)O'>$"\'il 1 .0229 0229 _ . ; i_ -_ ; _ 1 3/8 | JU . .0200 0200 11 10: .0040 0340 W 0.9360 _ 0.9300 |_ . _ E 11=2aGO .0711 1.1250 1.0539 9 0711 1.1250 1.0539 01 0 1111/4 10174 9 .0711 0711 1.2500 1.1789 11_ I.:'!- . 0800 1.3750 .0001L1.s750 0800 1 1.5000 0000 1.5000 0915 .0915 091 5 .0915 1 067 __.1067 1 067 .1067 01111 Drill ' Qiwn Size ' Ull.-U Il'l\lllll\'U' 1 117A Clearance 3 1 -L A-I 1:n _ 5v-uv 14 H 773/47 3/4 Ē1212 h '77-'57 1 fl L l]"'I I iii. . JĚ. CJ'JCD'*J . ..|.' L' . 1. 0-54031" 9/1%; 0.1015_ 1 0.1375 0.1959 _ 1 0.2254 1 0.2254 0.2034* 0.2834 0.3430 0.3430 0.4019 _1 0.4019 4 10 ' .0400 __0.5000 __0.4000 0400 0.5000 0.4300 1 15 . I/2 00/10 10 A .0400 0.5025 0400 0.5625 0.5225 1 .. 14 .0457 5/8 14 0.6250 0.5793 5/0 0457 0.5793 __ 11/10 1 1 11/13 , .0457 0.6875 0.6418 0.3413 1 "J00 \I 1. 0.1075 0.1875 0.2100 0.2188 1/4 5 Ăóý 23 7 .0246 0246 1 0.2500 1/4 5/13 1 22 22 1 0291 5/10 0291 ` 0.3125 0.3125 0.3750 0320 _ 0.3750 7 3/0 57/3 1 20 17 .0320 7/1fi 1I 5107" 13 __7/16 0050 0356 _ 0.4375 0.4375 _I' ,';.'.___1 "__ 3/16 3/13 32 32 7/32 120 28 _ In: En 1 5 0.1373P 1 2 -1fänhn' nnnn I 0 55* 1 1 V I17 " 1 3 11 1 Num. Nom. 1Thrcads 1Thread3-1 Basic Dia. 1 Ęper 1 D|a ' _Depth II -1 005111 1I BSF 1 icci: "RF 15551 7111-.533 Thread 0.5.1.1) (inch) (inch) ' (l.)¡.i. I _}Ž 9 1 1 0_1601p 0.1301P E §§E \LUUJU Z 1 (nnmsu sninunnu (_BRi_Ti§¡'i 3T|1i\i0|'tR0 HN:) Fii\iE) 1_1 I\" 1-"-"1 BOLT IBOLT F 103171311 (BRITISH s7/mu/\|=1 STANDARD WHITWORTH) _ D WHITWURTH) - f\-lfl|"\fl ` 1 . 0.1001P 0.1601P 0.1373P 9-13731" ¡ .i 1 1 ___ ___ ‘Ĺ_' _-_ 5/15" 5/16" I _40_ 40 7/8-1 1 1/8-1 1/2 _1_ Screw Size I SheetThicknesI ' size ' I _____ sWDrill)Size ___ oriii sneer rnieimess ND. I f] 'N11., 1... NIL I.-1 I„-.-,.(_.-:'.".;'::-1 1 12° =I" -R (inch) (inch) -WI-\ \ 3 \\~ 2.8 218 J # 47* _I I ___t'i*ŽfI7 _. _Recommended Drill Size Sizes 3-3 .“Reeemmended Drill Sizcs Sizes for =5 :15ca 5: :3mended Britt I-'ID U5 SIJ 12% II I I Self 5:55:55 for Wood Screws Self Tapping Screws Type 'A' P.Si mtłłłkw ng \ Mze - /vise M28-IV36 M 40 - M45 M48-N52 Šš -Ä-Ä@S Šš ETI-I> I\|U'I M56 - M60 M 56-IV60 2.0 ' \ I I 1 _m__ k 3;4ro:1e5:n-~.¡¡;arn.i-JI=1:-uanro: B Rake I' 1 [.._ . _ 13° - NEGATIVE 1 _M22 - M24 . ___ Ll 11.2a-~24 5 _ . _ (nur: 1. (111111 _ 7/32 -1/4 1/4 s/is-3/e___ 5/15-I_3/0 1/2 » 9/16 I/2-9./l6_ LI 5/0 - 3/4 5/8 I 1 22 IA1/2° NUT ivur ACTION Aonon I I 5/32 5/32-Q/@_M4 - M5 Wi_M8-II/7_ - IIIIIIII I a/az" __a/32" i i i i íí. wi-.y __ I I -I H\ nu ——I"_" I/U4 r/'64'f_1/3" 4.0:: 3.3 3.3 4.1 i 1' z___ I i ##40 40 " "Ll M.“ 517: -Ji/f_:-q_ P~?_ ..... # 30 #30 3/8" iiflmml (10mm)_ .313" 1,1 iu I lllll 1/1 e" mmm) _-....~-J~a»a_'.'.. ml/2" _!Z2.". (12mm) (12"""l.__ 10.5 4f1n 71-1 1:" r-11.-..T __—' "A5 n _ lL.U iL.u I ; 13.5 of (mmm) 17_5 55/s" /o"(10mmL%)_17_.5_ #20 — (zomm) ; _44,90 IT "##10 10 I 3/4" izommiw 2121.00 _ 5.5 .. II. #2 #7 25.5 ..-. _§.-.6. pl/_3$'_.I?Z!!!!!!1 _7 /E*Ĺ' .l.??.I'1ml I 23-5 5/32"? 5/az* i 5.5.5."" = _-Jl32 . I I(_ 1/4" % 3/15' 7/32 2.45 2.45 " —-.-$"F\.L53 1/an 5.5 6.5 I1 FF 5 1" 1" (25mm) (25mm) 27.0 27.0 7.0 I A I "Š z Oz; E-"MI U.\J 0.5 9.5 12.5 12.5) 15.0 17 5 I T7-5-" W 20.0 £1 ormcusrons PF, or Ę9!!!'!Ë!*_B.°_'" " '_¡_/-__...COUNTERBCRINGI Fi'counrransrmnno _ _ ____P!!* 'Ë'!!ā'P*!å GUUNTERSINKING |=on FUH socrnzr SUUKET 0240 HEÃĴJ cm» GAP scnaws $l.||tI:Wb *_ Counter Bore "W U I" L owe 4,66. _>lCl+_ /// Counter Sink 11.4/ I ///C ' 02° 7 žczI E. 0:1: 9_ 61 = 62° Countersink Coulersink DUCKBI Socket I1EHtl Head Cap Cap bCrBw Screw au|..|u:t Socket nuau Head uap Cap auuw Screw -1 ||___| I___ I_____ - C! 1 i D 1 ! 1 i Clearance For Thread .c, _ . . L . A. Z O0 29.-9 _ . ..| I. . . 26.0 M24 M27 _jeo WU -60.0 1 M60 66.0 M30 330___ I I 1. 40.00 40 43.0 46.0 48.0 . 043301 = 0.46601 = 086803 -666 _ ; 1 ‘IF . liva ‘Č 5 -I"I0l8 5-i-oioe 6: ;T_ . . . 1 -1 .-C ni 61'-Ä-4:i T. .4 . = = = Dfiwlrz = CJQUJL n - I I 0.18164 018164 0.55902 0.40451 0.29389 029389 4 A\ \v ,-l\ Z ‘Hi ‘dl 1 . . ,Ĺ (-Č) 4—¢ > .5 E' 3 16/62" „lie 1:51 4: ĒL 43: 4 = 0.46601 043301 = 0.25000 025000 C'0.:1UU:I: 3I1=- = 0.50000 o.50000 -4!. ... _!' 1!'-\r" P lältlDé B 11 21*" H. II 'HA " »Q se %'-"--%F 1 B @1317 » ,4A . —I»-> Q 4- / AQ A' 0.»,0 vq \W I 1. \ ar =Šš" O .35355 =0.65655 = II gig 1 6 B 11+/1 11 (+4 +1 CD '¢W3> GD B3>- =0.14645 = 014645 - C3 Gil- __.l 'II + 6W` ~—1-—"—" li1MilMi1lHi1 lBi1lH 'V l _.i . . IL '1' , ~>| D 0.701" K 1' _ 7 0.761" 11-Hole A = 047075 0.47075 1 2 . - ‘_1 . - . _ In VI .v1i/"'' _ =in'‘! gr'); C: "~" ==10 Il 1'C1tz He4.~S" W' Ouf .p_ \Y I- wA 7'F4 gel 1411 ‘JCI 551 @fi' B 'I' " WRIYAH 6% = 0.25000 025000 = 015451 0.15451 ', _ I w 7-Hole -Hole = 0.27052 033922 tn):-| = 0.66022 = 0.45040 045049 021694 = 0.21604 = 031175 0.61175 "^ I'<1|T`I'I|1©C(5JüC7"L = 0.60002 0.39092 10-Hole A = 029309 0.20660 0.09549 == 0.00540 018164 == 0.16164 FWCJHHÖÖRJQUJ C 4- _-;- T- -m I :3lZIG®3`7IT'r'I"`[email protected

removal, additional finishing operations are necessary. Flat Knuckle Teeth Roughing 01 'Il' 9-mi I' Ž $311K °'tii:1.T_> 'Š„l l_1¡¡¡_ "I" 1 iliII 1 .- 10.0 12.0 mm 5 mm 8.0 5.0 - 6.0 = 8.0 mm mm mm ,mm;mm 4.0 mm innn 2390 iaou FJ c: u: usc: 1 ...;_. 75-80 "J a n _ _ 021 025 0390 ce00 A 0.21 1 F' c o _ ~ F: u :-* 15_9'ż01 7960 15070 A 5970 A 47701 4770 3000 rpm,_ 1159201 rpm 3980 2980 239 2390 _ 1 990 Brass 75 009 . _ c: F3c:010 F' —* '_t'-Qt-Q_ 006 007 1 0.075 F3006 0.015 i F30.05 feed fe ed 0.015: ca 01 gs c:ow 1 0.07 1-mn' 1,141? I mm ..„„ 1aon7 .wo 11nn 1.30 2930 2660 170nn. .1„.. 9550 lÈ77o * 353011 noon Bronze/Copper 45 "" :1 Q2? 01 10.076 0075 0.08 . 1 s=0.09 $30.10 if i ffeed eed 0.015 1 0.05 1 0.06 '1 00.07 4030 3020 040 ,114030 30201 2420 2420 A 2020 2020 mm 151501 161301 C06060 cac:- K"c: ca 1 6060 1 4640 (Salt) Cast iron (Soft) 76-81 lpm 0.20'0.25 oncs- C3 CBc: 9'0.12 5'.12 0.15 0.20 !1 0.25 . 0.30 0.075 1 0.10_1 15611 0.02511 0.015 fe ed 0.025 |... 2. 2. . _ ..-_-] iT n7cni'ʃoon 'lllll"]l"'ii'1/lfifl won 2440 rp 9760 ,1` 4880 l c3660 ha2930 OD - . 1830 "'"'"l1 1460 "U" 1220 Cast Iron (Hard) 45-51 46-51 .;P'" . 0.18 ' 0.06 1 0.10 0.13 1 0.15 0.10 C3cC3 fe feed 0.013 0.05 j10.05 50 0.0101 . cC"c: 0.00 2440 100011/150% 1830 11460' 1220 3660 1 2930 2440 rpm Plastics/ Plaslics/ rpm 4 9760 44880 000 555012000 46-51 0.10 70.11 0.11 1 0.12 0.13 0.13 0.07 0.09 0 feed 0.025 1 0.05 ' H 0 70.025 Composites ž rnnwi 950 800 600 rpm l R57fiT_Q1Qfi 637071;3180 2390 1910 15901190 . 2 _J Mild Mild Steel Steel 30-35 1 10.10 I 0.13501015.18 oía 0.15 0.16 1' 0.06 777.1 10.00 0.06 0.05 0.05 feed ee 10.025 0.025 = 0.05 3660 1 27501 2750 `122007' 1630 5490 Y1 4300 4390 assoc 7320 5490 2200 ;1ss0 rpm i14640` 7020 1 rpm 114640' Carbon Steel 69-74 0.09 1001210015 0.012 0.015 0.06 « 0.07 0.075 1 000 0.05 0.001 feed fe ed 10.025 0.025 0.05 onvn on . non mon l 1mn" 7o'zn7 ::on I fmvn t 1nxn 1ccn .,W1.„,„ ...W ' nen dw . ‚t„o .wo 1 1onn rpm rpm 11 5520 5520 oven zivu Alloy 1 Ailoy Steel,' Steei/ 0.025 0.0255 ' 0.025 0.025 0.025 0.025 feed 10.013 1 26-31 feed B.01_3 _0.018 0.02 0.02 .1 0.025 High Tensile 600 i 500 1 400 430 950 13 000 1 400 rpm rp m*33180 180 15902 i 1190 950 Hardenedflool Hardened/Tool' ii 10.5 1F20 F? cn oowc: _0.01_2i 0075"' 1_ 0.15 0.06 007 0.07 feed 0.025 ed 1l 0025 . 0.05 0.00 . i1007 . u-1_ 10.0sY1—0.012 Steel 211% om nnn 050 1 .ooo oo.. 111 coo ..w_ 1 rpm 1 5370 Stainless wi ti 3180 Luuv 1e10115e0I1100= iuiu l1i:on Stairriess S EFEL=:7 30-35 O _ . _. oo 1 0.20 1 0.131 F? :Ž-*tomo A 0.17071 0.09 0.10 0.10 pi 013 0.15 Free M/C 3°35 = feed feed 10.025 0.025 70.075 0.075 Z0. _ . 1830 1114501 1460 .1_220 .i 12201 020 4880 2440; 2440 1 10301 rpm 920 130 730 1 010 61_0_ rpm 1* 4000 Stainless Slainless Steel/ H 23-28 feed 0.013, 0.013 0.05 1 0.07 0.00 0.09 1i 0.10 1 0.12 0.13 1l 0.15 Work Hardened 23°28 feed n|.. ::.. I Hllllllllllllll Aluminium/ Al Alloys A1 i I Irpm .pHl1;¢° vnnn vnon iuuu IUUU manna-\ cnvn Cfl'H\ 1 JIHU uvru avvn I1 fiiru I1 A'7'7fl "II IU I nnun @aun OPIOH UUUU "')flOfi LUUU co fifiifl U\]\]U 1 1 1 . A77 '111 i @ OD -I ' "JQC2fl 1 LJUU 1 LUUU 1 _ .1L _l\]UI' CD E CD .I] Fine Pitch Knuckle Teeth Roughing 1 \ H Ë)íh K"0 I'1'1JU G CD - Teeth cutter, yet requires additional finishing operations. Z (.D3U"l - . Suitable for Medium Roughing operations where rapid metal removal is the prime requisite. This cutter produces pmdutzes a finish that is generally better than the Round Knuckle - L LO Z ll I Suitable for maximum Roughing where rapid metal removal is the prime requisite. The cutting action produces short chips with excellent chip removal. As this cutter is mainly difficult to machine Also recommended for as high Si Aluminium. materials. Hole depth Stainless Steel, Tool Steel Bronze, Masonite & Resini' Resiw should not exceed 2 xdia. Fibreglass Laminates. &Titanlum-Nickel Siloiu Carbide Drill Diameter Solid_Carb1deD !L"P.R'"°1.°' 11 Suitable for both Finishing and Roughing operations on Mild Steel, Heat Treatable and Structural Steels with tensile strengths 5 1000 N/mm2. This cutter can also be used for short chipping Non-Ferrous metals. Usually comes with aavariety variety of surface coatings. 1 j J 1 as ii'!/_&-' "'1 wmwe nah, E :Šš §X"'\'§ 7T*-§/ 777 19%? :> 5-: I -1' anrn r-. 1/¢ -1 L?"-'13.7.51 mvm :'.j:7-F-i'¢-I A ifi |Ë1 4 ' Q-;CD Suitable for Medium Roughing applications on high tensile material where rapid metal removal plus surface finish are the prime requisites. itlt produces aafinish finish that is betterthan both ofthe above roughing cutters and generally no additional finishing is required. Ln -* @O')(3CO ¢3Cc vnn-1 |[J]|l UIUU 1 UUIU 1 "fUUU , ODD UQDH LUUU L'|U\J '77Rfl GRAD Lwwu O1fi ulu 1RGfi IUUU EUUU |\]\]U 1 1100 i Il\]U1 1_ Duick Spiral 40° Quick iFTT(\ (Dfifl uuu V" &X\ 1 ~l - Ll' UU Qfl UU Finfshing Soft, Tough and Long-Chipping materials. This cutter Suitable for Roughing and Finishing produces an excellent surface finish with no additional finishing required. Comes Comes in a variety ofsurface coatings. l LUIU \]1 1 \]\-IL' ' \] \]'\] 1:-' -.1. CD Q3C|\;| CH CD CD ')'1DI\ QQOH |_uuu 1 O1fl h 1 5551551 3."d Too' Life, Ue the 'be use of copiousquaoitor copious quaflifty of coolant coolaftl is recommended recommerided,| NOTE T0 enhan NQTE ::To erihan C'/c point to preventchipping ortlaking of the Carbide cutting edge. SlE;CDmCDm ED ED:.c particularly directeCDmQ_g; NEL:II:§ sa cmcz CIZ, e==s2a E ~11'ntt0 l h U i _ ,' Š Hlti l i i l tl i l tl Quick Spiral 45°- 55° Extremely Quick NXXXN9.2111 l§l\§*§\ SXXXXB JU Suitable for Finishing High Tensile materials up to 1200 N/mm2 as well as Titanium, Gomes in a variety of surface coatings. 'A91 #2 CCNVERSION mete _____ c0[1_17T1_0_|011_7110_LE__ c0Nv|s11s10N 711015 CDNVERSIDN TABLE SURFACE SURFÅCE / CUTTING GUTTING SPEED TD TU R.P.M. 7 ' ELŽJELĹJŠL10cutting Speed : Surface/ Cutting __20 25 77?1.i _ 30 __35 F -A U1 _ @_ 10Q 7;;_ -. 15_ 28 7 278 .7.7;.-.._=.1-8 -. 303. I: E5 EE.=3:IllIGI °°nona 'II'II '15HDCID:1: II-II. 69917.81 9|E: Feat pe: m inu1Ĺ_____ ea E: .Liina Ii'!GI CI}na C1 G? .. . Diameter 1_7 7,7710 10 - 1-18 16___,yS_, B2 1 98 115 . 28 33149 GB _-._1-.1.8 ,Spi,ndle gpiziiflè Speed speed (RPM) Wwýwrfl 0'7'.''1»:~_. 7 (inch) U06") 1 1 2305 _ 301 I 7 477 _705 795 1272 1590 72305 3101 397514 0771 5555 ' 0002 2, L... -... Ih ,. .,_ one _ 1nnn 11:0n 2121 QOJ 2551 CT)CD Q')-4. 1050 _ 1590 FT 530 .'0043 :'.'I'~.'.. "-"i:'_~..._'L-!:'fEr'. 15003501 i 25 Z€.J'I"-~I _ 500 000 1000 ?1266 1 1200 1 1500 _____ 1/0" 699o;-t996 _____2___ ml2-3[§7_1p.§99 1590_0300, W1__fl_0w,Ww_W_0__"W,i:7739071 4 239 239 398 _ 535 535" 795 A0 1193 __1900 1019ë0000 _1_500_ 1 4; 7" 2 33 77-77 Q10 318 U IU &ì\-LI 7| LILI _L_L L _-.: 1u1_d77_7l"";-57;. _L 1 J _ . 1 — . -.-_ .i. Z @U1 (D ....."."I'.' ,.. """". .. . .. .1 6 ' ;. | 117-" Afi -I-IA .. ____... _.. ..._ _____...2__i 1 __ . l'.'f\-I UUI 7I _~¢_____ . l rlnlfi 1 flflfl fill- 1 .. . J .. ... 00 ' fil*fl 1-___i - -----7-m 00 7 0 51 1 0331 ; _l U1, 7CD ___. ,_ ___,... . "'_' 1' ;-I51I\J AD /10 'TU I20 ' 202200000 025000000 00,42i11_220001fi l1 28 23 ___-_.-.--_8..------"p__;J22c-..1 300 1 7 8 1 10 16 8131212_1 39 2;;24?2-; iÝi_2 _ 470 0 05,5, 1 39 1 ÊD 'IE! OE O") Q l1 , UU '7l"'| HE I'D dd -I1-l I 300 ' _ _ 1 12" 1 OOU1 c.>u1U1 weoma, 3 1 5 _ 0 3 0 19201600/ " 0 U1U"lOD " CO 1 __ 26 31 31 _ 37 37 I 21 1 25 1 31 37 10 1 15 1 "21 07 ?"??"i'W' .n.Z -L.O-') NOTE : R.F!M. R.RM. for Surface Surface / CUTTING ( )

.ooo .000 1- _.o14 014 _oro 01o -022 - 022 *1Cd Ll) (idLO PO—¥ COO0 -I->- 16 I6 117 f . no5 SE3 9 he ha HII 1 I1 h7 "h A FF' hr; ha _ nnn l .vvv flflfl flflfl 1TT =5'=' u: .vvv .ıqvv 000' .000 .000 S _.ooo 1-.030 _ .ose - _.o2s 025 2-.030 55 . h11 .000 .000 .ooo .000 .ooo I " -_ .075 - .060 ooo ovs A(_- _.090 ooo "];1gI7]000 I .0007 .000 .UUU .UUU .UUU h 12 1 -.1oo _i y - .150 . 150 _ 12oA _100 1-.120 = kg 14.000 1+»109 +1 Z110 +.006 Ž+.009 +.010 kfi 900 +.001 000 +.001 .011 Z flfl O :1 ITJ E.I0J0 . _ Usi"na Q-_ I -.027 :1 --.1033 .033 -ole* I-.020 _ o2o I-.010 _ .o41 -.034 _osg .-.041 - .ooo .006 - _.oo7 .007 n1 __.o2o --.o17 Ull 000 _000 000 .ooo - .013 -.011 _ .013 .000 , .000 1000 .021 -.018 -.018 --.021 Čooo . .000 .000 - _027 _osa - 033 7 . flllfl .000 _.ÓÃŠ -.043 . .000 _.11o - .110 .000 .UÖU 180 --.. 180 I +.012 +012 +.001 +.019 +.023 ++.016 016 +019 ++.ooo_g+.o1o 008 +. 010 +.o12 +012 . +.o24 +.o2e ++.020 .020 +..124 +029 Tgleranceg Tolerances in mm 0 -I:or nu 'EI- eu -1 :ri: :::== :3:: \mr C10 ::a - .040 -.032 -.-040 -.032 -- .059 050 1-- .O73 073 132 I-.040 - .040 _.os2` 1-_ .07 .75si - .092 .92 -1010 020 -.016 -- .020 flifi .ULU |=on ANSI Füfi Äiiši PREFERRED PRÈFÉÈÉÈÉ LIMITS ¡.¡¡l¡¡TŠ a & FITS FITS (ANSI B4.1-1967, R1979) & 81 (ANSI B4.2-1978, R1984) 'll The following chart covers a selection of Preferred Fits (Hole Basis) for Holes & Shafts which will meet the needs of a large proportion of the requirements for Components, Standard Engineering Components. Rfl nu;|r Rfl Ëfl mm! uu Rfll vu un" \I\I UIUI to 80 S!-a. _O=:5UICID21:: 1to80 U\I lo 120 to1201 -'I an _ .ooo AA-.072 - .072 - .050 1-.000 1-.050 1-- .089 oeo _.1oe - 100 (1-_ .126 12s --.050 _.ooo i - .072 --.112 .112 -.134 - .134 -.-.159 g - .030 - -.030 .036 --.025 .025 L-.030 I ' --.1141 .041 1-- .049 _ .oše -.025 oso I-.050 _ -_.ooo .009 no: __ _.ozs .u:::u _1"000 1 .000 --.025 .025 ..000 - .ose 030 . Hole 81& Shaft Designation Symbols .058 -.058 neg il - .034 non - _.029 . 1 . H _ con 1 1 _1j1[]() .000 .000 -.019 -- .022 022 -.010» ULj r ULl"!' r\r\r\ 061+ 1 . .=1 1._ .!I .I .l"\{\ . .—-- ' r - , --I- r __ - LOOSE RUNNING FIT - Wide commercial tolerances, FIT-Wide used where accuracy is not essential. (RC3) (B03) _ . H*"/ H9 / II" da (RC) (B01) 7 FREE RUNNING FIT - High running speeds, large temperature . variations, heavy pressures and where accuracy aocuracy -ISis not essential. BSSO nitai 1 I 1 1 Ha / I7 f7 I CLOSE RUNNING FIT - Accurate location at moderate speeds H3 Ha / I7 f7 H3 (R04) (RG4) on accurate machines. (R02) SLIDING FIT - Accurate location where components are intended to move and turn freely but not run freely. „1 ,ga s*s„a¡„? H 5 / Q5 H7/g O'! . imal 7 5 ' 7 LOCATIUNAL GLEARANCE FIT-Snug FIT - Snug 111107 fit for locating locating LUCATIONAL CLEARANCE stationary components which need to be freely assembled and disassembled. 6 HH1// hnfi 3 H1/ lhézl;hfi U-02) r-\r\ L.. __.+* __ E -'___i si . .-1 _J 1 u.\._ Description / Application 'Bescrintinn/Annlioa-tion CLEARANCE FITS GLEÃRANCE H10/39 H1"/09 .. . - § H9/ H9 / II" U9 1 1 \ _ . TRANSITION FITS H7 / kfi I-I7/I15 +028 ++.O33 +.039 .039 ` +.045 +14 .033 +;+.028 .023 +.015 +.O17 ++.020 .020 1 + +023 þ+.oo4 +. +a 015 +. 1 + 059 +.035 +.O42 +,051 \ + .042 +.051 +059 '+035 +. pfi +.012 015 +018 +1118 1+ I22 ++.026 006 +13 .026 . +1032 +.032 + .037 I +022 112 +. +.006 +.012 +.015 1Z120 + +064 A +.I076 +.076 +090 + .090 +053 -+1104 .028 - +1035 +.020 +028 +.035 -+1043 +.043 1+.05s F831+. 1 C106 + +.3O' '+.036 + .036 025 +1030 +.020 +.025 F ++.006 010 +.013 +.016 +.010 +016 ...ttJ¥¥ls;t: +.047 +- .040 +047 +.o2o ` ++.034 .034 +.040 012 `+.O16 '+016 +.020 +.024 +1024 '+028 H 570+G7 +.012 .0 g +.012 ". +.0G9U +010 uuo1+.uuo +.uur -I".UU +002 +.005 +006 +.oo7 +2 002 +004 +n +.035 .030 + .035 +.o2s ++.3O .018 +.o21 +.021 +.025 +.012 \+015 +018 II }i7 +.010 -+1010 +012 +015 '+1 .000 .000 .oool .ooo .000 000 000 .000 000 .000 000 .000 .000 .

'515l=1"';°"'1„"e1-mi sm' Ala .-115 ' Ifirass ness gr9 Thicknessl I151333155--ar 1 Thick-I'W"I?II_lll 1 W 1. uz:/112 kgs/mi ^ kgs/ml f kgs/mi kgs/m2 1 ligs/ml Lbs/ft' A (mm)1 kgs/mi' kgs/m1 ITQS/I112 _. (mm) 'I'"'"II _- . -...I"'£"I. I {ill =5' It i 1 1 '71 1 0.181 1-44.. 1.44 „fl -1L 010 1 __.0fiv0 -89. 0.85 0.89 _ _ _ _ 0.31255 7.933 1 12500 0.3125 7.033 12.500 i18. 1_ 0.20 1.60 -1-1258 ?gU.2UgIfi'Ii.6U U15 if ff __'I.28 1.34 0.15 _.J-28 _ 1% 111.250 ' 0.2812 5 7.144 _ _ 1ł:?_3J.?.,j 7-144 - _ 10.22 0.221I 1.766 _0540 1.70 1.73 O20 . 0.540 170 . 1.78 0.20 1 0.2555 1 6.747 5.747 110.520 ez ~ 1.02 0.25 7 1 0.24 1.92 0.25 I0575 0.575 2.13 2.23 2.237 02500? I3-359 _ Ě;? 51°9. 5-35° 1 10.000.40.20 0.23 2.24 .>= _M0.3_0__11031_01_2.55 0.30 0.310 2.55 _2.57 2.57 0.37 II_1 0.32 0.2344 . 5.053 5.953 19-370 032 2.55 0.35 2.03 3.12 0.35 10.045 » 0.945 #293 3. 12 _ .19-E94 0.2137 5.555 5.556_18.750 3.04 3.750 0.38 0.33 304 . . 3.55 0.40 1 1030 1.030 340 3.40 3.5 5 040 0.45 3.33 3.83 I 4.01 4.01 0.45 1 3.52 5.159 _Ñ _ 3.120 0.44 012031 . 9.-2992.1 Q 2 4-2 -L 13333 CAIN? - '4- I ,9? .4 7.350 ' 21.25 _1 4.45 4.45 0.50 71.34-,5_t*71.25 4.1111 7111557 0.1375 4.762 7.500 "-5" _ Efl-1'7-ll"'II 0:1.5Z_Łf1lfĚ2 ' 4.53 4.537 4.90 4.90 0.55 0.55 0.56`1 4.43 4.48 11U.lIIU[0.1719; 4.355 4.366 u.oru 0.63 1520 510 . 5.34 0.60 __l.620 . 5.34 _1 _5.10 smo . i 0.53 5.04 5.04 3.050 9 10.1552 3.959 1 5.250 I.0 '-lU'DU'l-F. 0.501 iQO'?I'\ 4 3 __ GD I\J _-L $ Q 1 f\J 7?: \ł i 1 Name Symbol name Actinium 4 'J Ac A0 A9 Al Am Ar As At Au B Ba Be Bi Bk Silver 111111 4 ~44 I- _ . _ _ .. 0.357 4' 4.. 11 ' 1"lHlB Pizie 1' 4 1? 4. Tin Tin Plate Piaiz intro'(mn-11 1 Piziz Wl. g ___ I 7 :nn 1 I II Kl I I IIII FIHTB Piaie l 1 WT. WI. kgs/m21 (mm) _ kgs/ml {mail (mm} '1kgs/mi lrgs/mi! kgsfntz 1.2711 0.35 '1 2.33 _ 0510 1.27 0.531_ 4_53 4.53 WI I 1 Q3 i I 9I 10in .503/I0? $ 30 0500 ~Immi 307 0.0125 ł1 0.318 0.313 .U-50° 0.15 31 #010100 . .0 0 . 273 0.438 _0.273 4.99 0-438 |]_1g 0. _19 1.54 1.54 = 0.37 0.37 1 2.96 2.95 0.54 .;1 g9 1 „..'"7 '-Ě{„Ľ `}-."_{ Ž-. .-.-„ I.ID UJI-I 0.110 U.UU CI. IUĽ ; U.£-DU U _ 430 5.15ID I 3.40 u.uu I _32 _U.U 0.0102 u.4uo u.“ UÄUO :2; U.ĽĽ |.lD UJH 1 1.92 0.43 3.39 __1 9-70 .9-4Q . -r:cu-. 0.24 9".9.|>ov I33 __$.0094 0.375 _"-24 .*Ě 99.094 . 9.-338. U-238 _0375 027 3.6331 0.757" 0344-4 M43 0.27 . Z-J22 2.15 _ 0.46 _3.6 U-75 _5.35 5-55 Y 0.0086 0. 218 J4- 5.9-9939 I 0.21 10.3 2.24 .9 c.riQ coQ 6.24 0.50 -~ ~ 0.28 0.80 ^3.90 .9 77r .u:. M 0.00737 0.103 35 0.0078 0.198 0.313 0.313 -4-"' ' " 1 in0.“ :Q fa 11 no'it .39. 931 '55: 2.43 . -1.11 u.:ru I "A 35 35700070 0.179 0.231 EI 1132 0:32 2.56 1 0.571 0.0070 0.1703 .9at -1 4.50 1 1.00 7.80 I (mm) .-.-1 4, '-39:' 1 it I n nrn 8 A I'\ Ann 4ll'\f\ n l\'I' nn l\'F? ? _I 4 -I in W!" l L.-'TU 54 n-I I-I AA |\ 1 A nn An n Ii on FD (I1 F0 1 '1'-II /1'11 fl DI1 u.;Iu ' I1 '11 u.u| 9 I .._ -fly; . ..._.. ;.i.-~.'"'". _ *\--.1 ., ._-11._ _»-..;.-, 1.-. /' c >111- -._.>1, .~.,. -..-;.'-; -1. if -1 15.-r_-,>»1, - , -. 7..4 -.,., .: '-1 .,, ;:~~.'. .. . -14.1.4-4' -4,.-3': -.1.1. -77>" if-. .4 '2 Y\.4-2 4-_.-= .'. 2. 34." .1.'.1; " æszg .: .> _:. ,. . ' _ . _ 1 _.. :11 6.. _.1 1 1"' -r'"»,3I'?"?, 3 ' ' F -tr li Ii E IS ,. A _1.-1.!_ IH§LdLIIIU 5' L1 ? , _.-'5 4 eisminh 31311111111 Berkelium Bromine C Carbon Ca Calcium caiaium. Cd Cadmium Cerium Gallium Ce Cf Californium CII Chlorine Cl Cm Co Cr Cs Cu Bu DV |-.. I-I I Curium I Cobalt Chromium Caesium 1Caesium Copper 1C0pper Dysprosium 3.(- He Hf Hi Hg 3 Ho 2 g l1 3 in In f lr K Kr E >.5-r .5 La Li Lr Lu Md MCI Mg Mg _ Europium Fluorine Iron I iron Fermium r.. _.._.;.. ... l'ldIIbI|.IIll Francium Gallium Gadolinium Germanium Hydrogen Helium _Halnium Hafnium 1 Mercury 1 Holmium Huimium 11150153 iooine 1ilndlum indium 111m11um iridium Potassium lPotassium SymholI Name Symbol Name Mn Mo Na . Nb Nd Z Ne Ni No Np N0 ` 0(D Os P Pa Pb P3 Pd Pm Po Po Pr 1_Krypton Krypton 11Lanthanurn Lanthanum 1Lithium Lithium 1Lawrencium Lawrenclum Lutetium Luteflum 11Mendelev1um iviencieievium Pt Pu Ra Rb Re Rh 1-in Magnesium Rn Ž Symbol Name Ru Ruthenium Manganese Hu Molybdenum S S I Sulphur Nitrogen su SI) I Antimony Sodium SC Sc I1 Scandium 1 Se 56 Niobium Selenium 3¡ Neodymium 51 Silicon lit...-..._ INGUII Neon 1 Sm sm Samarium I Nickel Sn 5,,. Tin I Nobelium Sr 1 Strontium I Neptunium Neptunium Ta I Tantalum I Oxygen Tb -1 Terbium TC 1 Osmium Technetium I Phosphorus lg Te Tellurium I Protactinium Th Thorium I ' Th j Lead Lea CI T 3 . Titanium Paiiadium ' Paiiauiuiii Thallium Promethium § TI T' I Thulium Polonium Tm Uranium Praseodymium U 1 Vanadium Platinum fV I Tungsten Plutonium W Xe Xenon Radium xe Yttrium Rubidium Y Ylterbium Yb Ytterbium Yb = Rhenium Zinc Fihodium ' LII Zn Rhodium Radon Ě-1 Zr Zr _Rad0n Zirconium 1 I-.1 CT 'BA-l4u.r.-.'ì\ I'TnrI-\I||v~r~| IUIUIUIII E IF _||_ _I! __-_ 1': r. K 'Q 2 Thixotrngic : Describes materialsthat materials that are gel-like (e.g., Toothpaste) at rest buttluid but tluid when agitated. Thixotropic Centigoise (cps) (ups) : itlt is a relative comparison Comparison between the viscosity of water and a fluid. fluid. Water is the Centipoise is 1 cps at 21 21°C standard by which viscosity of all fluids are measured. Water is1 °C (70°F). Fluid Approximate Aggruxiamle viscosity Viscosily (cps) (ups) wa1er@ 21°C (70°F) (70°F) Water @ 21°c 1 3 10 Kerosene / Blood 15 Ethylene Glycol / Antifreeze 65 Com Oil Corn 150 30 / Maple Syrup Motor Oil - SAE 30/ Motor Oil - SAE 40/ 250 40 / Castor Oil 1000 Glycerine Gycerine 2000 Com Syrup /' Honey Corn 5000 N|0|ăSS€S Molasses 10000 Chocolate Syrup 50000 Ketchup 100000 Sour Cream Peanut Butter 150000 1000000 Lard L414 5000000 Caulking Compound _ 100000000 Window Putty chan 9 elntem NOTE : The abovetabieis abovetable is intended as ageneral a general 0guide only.V.Viscosi Viscosity varyY with change in temperature NOTE:The uide onl W values var P erature Milk i. I -. lliscosity Viscosity Chart tor lor Common Fluids 5 me 23 -0000 10.0155 0.397 0.397 - 0.625 .21Ě 10.0141 0.0141 1 0.357 0563 \ 'viscosity: flow (usualiythrough a specific oriiice). orifice). iiiscosig' :AA measure of oi the resistance of oi afiuid aíiuid to toíiow ._ . z:-t1. Symbol; Symbol Name 1_ Erbium Er I`_Einsteinium Es Aluminium '; Eu Americium F Americium Fe Argon _ Fe .5. Arsenic Fm Astatlne Fr Gold Ga Boron Gd Barium _ Ge Beryllium H _1 -4"_;.. '-_1:¢' :-' -." SYMBOLS FOR ELEMENTS Br 4.00 I ZMIGÓUIÓĚFNŽ-\Š GU, '_;..:.' :.:_ :1 4 -. ¢. .r-.'.f .- -.";'~ .'1Li;'. 5.1.-1 IIIIII IIII M . -1: --F .3 ;.-'-._.~.' ~:- =11 5 1&1 Y! 1 ,,-._ _.. 0:--1.1.-"2.1--; .-.-1 -I-..,,.'-'.1/,' -'-,-'~' 7.1 . . - -.: :4.;- 5"' ~;11*. -"5:-4-1"1.--- -:-.- 1 E i — .- .-»-, .r .» I i7 i 31g "1 Wfiillhfi 1_ Wfiioltt, gms. lbs.1 lbs. 1 °"'s' er per Pfllj per METAL/ M5ri1u.o1o METAL/METALLOID Point P0 int ce C" Brinell C0nductivity Bnnell onduclvrty 1 Expansion Strength?Hardness" Strength Hardness' Hear 1 Parr" F" tonsfln.“ tonsfinf HB OU -100 = 100 ' 100C 100°C Cu - BRONZE (Cu 00%, 90%, Sn Sn10%) oeonze 10% 05 35 125 1_ 20 20115717 0.30 7 S3 28 100 _lIflfl Phosphor Bronze (cu95%,sn4%) (Cu 95%, Sn 4%) Tobin Bronze 11 1 5.3 550; 550 1047 1942 8.8 1942 E 'UH LNIIUU /0 IU/U; 3.41 5251 $20 J'; '-_4 c1\ow1|uw|1cu) CADMIUM (Cd) 1-'-I1 I'-J (J1 960 GDCDCD 1760 . .¢ "-~lCD CD 3.5cn 540) 321 __610 .r=~.c:1 021_ 9° 01 7 1 1.6 1.5 101 101 850 1562 1552 cAn3oN(c) 1Ě 134 055010455. 3550 154551 CARBON (C) 2.21104 Ě1í1oMiuM(cr)" 5.7 1í'31 1505 1ĚŤí° CHROMIUM (Cr) I 6.7 4191 1505 2740* 003411100) 3.3 550 550 1483 1453 2700 coerur (Co) 2700 8.8 COPPER Elect7olytic' Ele 5rm|y11z1cu)1'5.91557 (cu) 1 8.91 557 1082 _coeeen 1032 1981 . 00042070110 {Cu |ou1=..fl.1.ur4.1r4 (59 4.5%, 4.5%Ž 11 ` 1?1 Mn 2%, Mg, s1, 501. Al.) 2.01174' Si, Fe, re,r>a1.A1.]_ 2.5 174 00011112 500 11112 5oLo (Au) (Au) ' 19212041 1050 10715' GOLD ' 11 060' 1945 ouuzmem (cu 00%, 33%, 7 O sun menu (Cu Q11 199/. 7n 2%) on/.1 Sn10%,Zn 1 8.5 534 1036 19001 _'1"-'L 1 mon (Fe) (Fe) IRON 1 7.8 490 150512705 Pure Iron 1535 2795 7.0400 Wroughtlron 7.7 480~ 1510 2750 Wrought Iron 2750 , 7.714001510 Castlron 450 1259 2300 Cast Iron 7.2 4501125012000 Malleablelron 7.4 462 1250 Malleable Iron 1259 2000 y A_ 7.41402 2300 LEAD (Pb) (Pb) 11 .31 707 020 LEAD 11.01707 326 020 620 nihouesíírhí) ' 103* 070 mnonesrum (Mg) 7 " 1.7 '10s' 670 11240 1240 1 70147511220 22401 1100000000021045} 144054953: (1411) 7.5 1 4751 .25.7 Š;/1:. „2«„ noweoenumimo) 10.4 651 551 2500 2500 4532 MOLYBOENUM(Mo] 104 4532' MONEL Moon (N167? (Ni 57%, Cu cu 30/ 30%, 1 1 c3%,1>z1. rz,iv1r1,s1) 3.31551_13152400 83% bal Fe Mn SI) 88 551 1015124001 (J1 Q0 CJ"l u, I-Ill-1U, C11 C10 .1'::- -L CD C0 1 P T'i; 7.-_ 9~ .. _ 'cl MUNIL IVIhIPlL1UU IJ'U'15, 26 1% 100 - 30 Lil 1NlCKEL(Ni) 0.0 NlCKEL(Nl) 8.9 550114542050 55611454 2650 PHosPHon0us(P) 132145 44 44 111 1111 PHOSPHOROUS (P) 1.82146 '1PLAr|rírMr(P1) =u1r1nun111 11 121.01100011770102121 *'121.313301770132121 "-1 .3: '1' '-1' 1. 1', 91,, r. .5 .-.'- -.,-.,'r- -.',.. -' 2- '. _ . 12. 43 -la.DO _ 4.r=. 20 34 23 1_ 04 0.30 0.00 55 55 18 A.._ 16 0.08 I 0.00 16 350 125 30 30 30 Hr 100 1 100 100 0.18 25 25 30 25 9 - ` 29 26 31 (JO _.1 -.-_ '1 . -. .-1' .,1 __ , :' _'1 _ _ . . .\. ~- < ___ 25 34 42 7.8 490 1371 2500 12 45 800 300 40 J> O 1427126001 7.8 490 1427 2600' 7.9 495 1398 2550 7.3 458 2321450 7.37Ž15372327' 450 1 30 50 217 140 160 ___ . 1l _ . 1 _L -I5l\J 4124 1-01.6 l1 0.06 0.19 06 0-19 _ 1061 13.3 14.5 1 13.3 i 14.5 13.3 14.5 1 0.12 0.12 0.12 - 1 0.12 1 (I) Z U5 'L (II I\.'J _ 1 130 170 201 7.9' 2450 7.9 495 1342 134212450 1 7.8 490 1427 2600, 142712600_1 1 _ 111 1 7.8 490* 490 1483 2700 7.8 490 1427 2600 142712600 rm (Sn) I 4 {fw 717 57710100171)7777 if 4.5 02 r|rAN|urvi (ri) 4.5 20111000 281 1800 0270 3270 runesfiãri (wf runosren (w) 101110104. 19 1191 3400 61521 _ ge->æä VANADIUM (V) 5.1 000175010102' 330 175031332 'vanAo1urv111r) 10.1 ZINC ZINO (Zn) (Zn) 7.2 447 4171735 13 724471417 700 710 - - A -15 1 10 16 6 _ 0.2 0.2 17 13.5 17 0.12 0.12 0.12 0.12 0.17 0.17 0_ , 0.21 OĹ 200 -230 0.08 204 0.04 294 I 42 31 - .-10.10 0.10 357129 3011 0.00 0.33 05 120 00 Common Chemical Compounds - 0.22 Common Name Baking soda Black lead Dlnunhinn Bleechirrg nnurrlur pe'-:der Blue stone / vitriol ltlue Causlio Caustic Potash Causlic Soda Caustic Limestooe Chalk, Limestone Chile Saltpeter Crystal: Condy's Crystals Epsum Salts Salls Epsom Vilriol Green Vitriol Laughing Gas Lime (quicklime) Limewater Limewaler Liquid Ammonia Lilharge Lilhargc Muriatic Acid (Spirits of Salts) Oil of ol Vitriol Oil Red F.erl Lead Sal Ammoniac Ammoniao Saltpeter Saltpeler (Nitre) Slaked Slakerl Lime I|ĺI\'l\I|lIIIu 34 _3*. I 71 -L 1 'CD J3 1 45 147 . .|. -5-"\I O 125 -I=~l'J1 il- \'J 1 00 60 05 85 _25 00 30 - _ 11 1 fr:,,-44. 5,'-' -"1' ,»!' "...? "L 1 .O. ___ na 0.13 13.411 - 1 JâŠ 63 - 4.4+ 77 \Ico\r.|> 12 57 20.6 20.5 67 10 100 15.5 100 5.5 15 1 180 150 12.2 2.2 24J:-U10nl\:r 110 133.31 110 3.3 5ou ¡\-,_a r.1. r_ \ . PF' co 1 8.9 40 '40 1 1111 50 200 58 ro*Ä1:::°c: c:c> - -3.2' Ĭ-5 0.21 981. 0.12 0.12 1 25 _ 60 1:*-;'1:.1; " .. '-.» " 3% Ii '-§_-.3' 1: ¢1'-i~.'.- Z11; F. _ 29 __ _25 (>ne @CD 1 ,. -I' =1 17.51I 17.5 15 15 2.9 -- I" CD _ nn\I , 113.530 0.12 0.12 0.11 0.11 0.11 $3 Łh)(AJ 1:.: urrun coco0- - -0 0-J. 0.12 0.12 on ® Ca-J *-J 1 6.7 I .. ; 3., -:-._ -'-'-.'- _4.8 1 4.0 ý4.8Ž 4.0 _ 2.4 1420 25001 25861 y - 2.41147 1-420 _10.5 110.51. __.i_ 055 15 _30 00 555 000 950 _ 1702, 1752 1 _ _ _ _ STEEL Low Carbon Steel Medium Carbon Steel High Carbon Steel Manganese Steel [Mn15%,C1.5%, (Mn 15%, C 1.5%, Si 0.2%)' 0.2%): 1 Nickel Steel (Ni 3.5%, 1 C 0.25%, 025%, Mn 0.8%) Cast Steel Stainless Steel 0.21 45 'w1unrzn15n1L(cu50%, ` O 1211400.) 0.415251 zn40%) 341525 000 900 10521 1552 22 22 I 'I 1 21 21 .. _ — _ -L CDCD CD 1900 (011 _ SILWĚR (Ag) SILVER C40 Z 25 1 511% (ca) .°"Ľ°"i-- \.lllll 0131 _ 25 8.3 517 930 17061 1706 (cu 70%,zn.3o%) 7n 'JflU/ SILICON srucon 0.26 _ U-|._LIU1LO 11 (cu 00 fprr 'H10! 47 47 QTIIIII U I l-I-I- ANTIMONY (Sb) inmonv (so) BRASS Yellow Brass Cartridge 55 155 -1fl"1'jl 7 7 481 10401005 1040 1 1905 T4 -4 401 1 . Manganese Mangarresc Bronze (Cu Mn 1%) (50 60%, 50%. Zn zr) 39%, 39%,iv1n 1%) 8.3 3.3 522 522 87111600 871 1500 '- 'a' rel="nofollow">_,, 23 23 -_ ; 1 ,1w',. :_.,:_ .,_. 7WBi _! _l0Ii1 W7!¡_9||Ě__ Melting Melting Tensile Tensile 1 Brinell Conductiuity1Expansion Conduetivity1Expansion lbs. Strenglh HardnessmElect.1 *$ gms."'lhs.» Point Strength1Hardness1 — perper cent gms. per per ;?il_approx.)l ?2(approx.) (approx.) (approx.) ' 1 cutt C" C° F" F" tons/in.' tons/in.“ HB 100°C METAL/ METALLOID METAU METALLDID 1 7591. 1'0.25 Pure Aluminium (Al 99%) 1 2.6 1051 PureAl|umil1ium(A199%) 165 050 1220 660 , 1220 Silicon Aluminium (Si 5%) 2.5 160 6301165 630 1165 Silicon Aluminium (Si 10%) !'°!"!\° J2:-U"lO'!I 155 I]\J1JDU1IUl'J1 580 1 1075 -IL'): 7 (appmx_):(appmX')l I'IB3I EIBCL1 Cl ALUMINIUM ALUMINIUM (Al) (AI) _,_ :..;, -. . ._., '7'7OF '7" PHYSICAL PHYSIOÅL PROPERTIES OIIVIMON METALS/ METALLOIDS COMMON METALLOIOS 1 Melling Te Tensile Melting nsrle 1 P _ cm" cult cu tt °:l:l\\l_ llnnnflninl-n IO}_ ciflflf IJIIII.|Ullll"11IIIIIIIIIIl.llll LOI IU.r"O W __.,;. TH,-__ -.-. _ . -.-_ . _ ,.. I PHYSICAL PROPERTIES OF PER 'I. COMMON METALS EI _1___, šl > I-rrr E! " =,__Uen /_ METALLOIOS EI þl ,..¡..E! :Iua' ra Ě!, E ___ I ..,,. .1 1).;-+'= .~;'F I;'_.'1'.- I-I -;'..Ě- -.1112: fl -. :1 2 0.00 .Qooo 0.25 _C>Nur „... ¡ ('117 f\17 U.|r P Goz 0.13 {:1ca—~ E:co or 311.31 15 - 18.8 0.13 - '13 18 FD Z CD _ 15, 0.09 (J'I' Z'I 1 I1 1I 1I 1I 1I 1I 1I1H PU"'"U' „mm Vinegar w„¡.i„„S„„„ Washing Soda Chemical Name Formula NaHCO„ Sodium Bicarbonate NaHCO„ Caroon or Graphite 1C Carbon Calcium EZ ca ::».. "2,2 CaOCl. Calciurn Chioro-hy Chlerozhypo Chlor¡".e1 1:: 1:: CT) CuSO.,5H20 Copper Sulphate C')coC7 CDCD P Q2 E: Z KOH Potassium Hydroxide KUH NaOH Sodium Hydroxide Na0H Calcium Carbonate 1_ CaC0, Sodium Nitrate ^ NaN03 Potassíum Permanganate Perrnanganate 1_ KMn0,, KMnO, Potassium 1 MgS0,,7H,0 MgS0,7H2O Magnesium Sulphate FeSO.7H2O Iron Sulphate 1 FeS0.,7H,0 Nitrous Oxide N20 Calcium Oxide Ca0 C00 ot Calcium Hydroxide _Ca(OH)2 Soln. of NH,0H Ammonium Hydroxide .1 1111,00 PbO Lead Monoxide P00 Hydrochloric Acid HCl I-I' EQ1) Sulphuric Acid Trinlumhir Tnlmvínń Triplumbic ...,.,.,.,.,.. Tetroxid .,.,.,.,.,.. R:|u Ammonium Chloride Potasslum Nitrate Potassium Calcium Hydroxide Acetic Acetie Acid (weak) (weak.) Sodium Carbonate 1.~.~\x.»'~;1.=- 1171,-' ~. 4 I\Jcn H,S0, 11,00, H I u3u4 .Dh „M 1111,01 NH„Cl KNO, K1110, Ca(0H)2 Ca(0H), 1 CH3G0OH CHSCOOH 1 Description White powder 5 Black powder chlorine-smelling powder white chlorine-smelting Large blue crystals White deliquescent powder White deliquescent powder White powder White crystalline substance White Small purple crystals coloudess crystals 1 Small colourless Green crystals 1 Colourless gas White powder iiquid Clear, bitter liquid iiquid Strongly fuming liquid Orange powder Strongly fuming colourless oolourless . liquid iiquid oolourless, viscous liquid iiquid iiquid Heavy, colourless, Eirm hzmuu mfl n/\unłzr ...„„ ,.„,„, .W ,M-uo. ` White crystalline solid Crystalline solid White powder [nn I1nq\ru |"nrI r\urInr IIIIU, IIUU-I, IUU PUTIUUI Brown liquid Na,C0,10H,O Na.CO„10H,O 1 Large, white crystals 1;. .;. 3' . .-.'«f«..'»»w.--.í»„1»1..v.. .1- -..- r: =-.- '-.-1: r"- = 1. c- _ .,.-". = /.. ,1;-"-.1 J;74- '1. 1 _1 15 12 1:1 _ Sheet--00070-5 Sheet-Gauge T 1 7 SHEET METAL BENDING III II l"|' l'l1 -I iš Ifl -|I> ,_ II I'l1 I: EE IZ lh ALLOWANCE Ih ,_,_ G: :EIh I: {Ď I'l'l Wire-Gauge To calculate the Flat Blank Length (L) - 90° Bends '.,,___uss1u.' ,,___ Qeiaiaanrzee lezlrizrlized 1 722111117777315517 Zinc" *I Sleel Briiish Music 'm"" Sheet Sheet if Sheet 1 Gauge 1 W.ire Wire 1 Std.Wire Sid. Wire 1 or Piano 'Ä ýGaugel, 1, I W ñ0auge(l.l . ' G 1 Gauge _ ' ' 1 ' 3.0 1.21 3.003 0.1160.110 2.95 2.05 1 0.0261 0.020 66 0.00 10.1091 0.1031 ý0.109 0.100. 2.75 1 0.023 1 0.71 0.100 0.104* 2.04 0.029 0.74 122.00 10012' 91074 1. 12 -2 . 2.75 0-1°21 -681 -141 ~64;°-02 1 1 . „1:4 13 .....+_ 0.9941 009L2.37 1 0.101302;* 0.31 0.031 A 0.79 A0004 0.093 2.37 ŽÑ32 0.31* 10.092 0.092'? _2.32 2.32 T" 0.092 0.0921 2.34 0031 0.70 14 10.073 110.078 0.0701 1 14 2.03 0.0301 2.031o.03310.3-4 1 1.99 1.99 10.0331 0.0361 0.91 0.0301 _1 _ 1 Ž' 0.080 2.03 0.080. 2.03 0.033 0.841, „ -.A0.079 1 -ion n 4 71' /1711 ' 7 1.02 1 n 15 1 1.uu 1 0.0-rui 15 0070 ^^71~ 1.00 0.0401 1.uL 072 1.83 1 u.UIL1 0.072n 1.33 0.035 U133 0.69 u.u1¢1 1.00 L001 U.Ud3£ 42 . 1 __.,":.. 10 1 0.0321 0.002 0.034? 0.004 1 1.31 1.61 1` 0.045 0.04515 1.14 1.14 0.033 0.063 ´_1.59 i 1.59 1 0.034 0.064 1.33 1.63r ´ 0.037 0.037 0.94 0.94 1~~------i RR 0.233 7.19 10._300A7.021 0.300; 7.32 0.0101 0.25 A l l_=L1+Lg-O 1_=L1+|_2-Q Also LL = + 1.3L3A150 = L1 L1 + + L2 1.2 + I 7470219 1 0.219 1 __Wj10.2031 0203 if `lG-1rmUl&uC-¡15:l\-7c.o1M T 0233 10.2731 0 *77.01 1 0.011 0011 0.23 ,Q1 263 21 63.37 ' 67 _,,:?.761..'m__.:. -- 0.0031 0.15 . 0.2441 3.19 0.2521 3.40 ' 0.0121 0.30 02441010 0.252 0.40 0.012 0-Q°.U»15 0.008 0.20 0.225 0.008" 00.0131 0.33 0.225 5.72 5.72 0232 5.89 500100173 033* 0.010 0.25 0.207 0.0101 0.014 0.330 0.207 523102121 5.20 0.2121 5.331 5.38 *0.014 0.36' 1-7 170.0121 '0.012 0.30 1.. 0.1921 4.33 4.00 0.1921 4.88 . 070131 0.0161 _ Z 0.307_10.192771 2?" .2 A 0.41 0 0.014 0.36 0.177 4.50 " 0.176 0.1T450 0.1701 4.47 4.47 0.01810.46 0.0151 0.40 0.2501 -- _ . 122.19... 0.234 E3 ru no L- 1: ¡'L?>1 1'1::fL_fi (mm) (inch) 1 (171111) 1 (inch) (171171) (inch) (mml 7 (inch) 1 (mm) 1 (inchllmm) (1...zr{}1m...1 (nicr.) (mm) 1....~..) (inch) (inch) (inch)1(inch) _a -L W_ý1ý0.281 07.231 F O "1191. -L SHEET-METAL ĚĚiz.81 WIRE :E ::Iin GAUGES 1:::>1: ininua rr~ Hi1MHlM1 1MlH1l M1 Hli Al ' ' Aluminium "m'"'"' Soft ęofl Steel ' _ = 7 1 marl-ii ' 1 ' . 1.0 1.5 1 1.5 4.0 4.01 3.0 3.0 10.0 10.0 10.0 15.0 10 1.51 15115 15 2.5 25 1 2.5 25 4.014.0 6.0 6.010.010.010.015.015.0 0010 051101. 1 C0111 HD1181´ 1.5115 10.010.01U.U15.D stainlesssty 2.5 2.5 4.0 4.0 4.0 6.0 10.0 10.0 10.0`15.0 15.0 20.0 20.0 Stainless St. _ 1 » 0 1 I I ' Minimum Bend 3111111 Radius 115111113 'R'n 1. 1 Minimum :11 -. M .125 I-.'1 .- : - _ -.- I '-.' .;-.-~;-_.i :, :3, ;. _-, 5- l t; .» - _ .- _ .1* :EGD ::I:I:en::|: 1:'U iš I'l'I -IIh ,_en COMMON METALS en S: ËĚ:Š1: :: WORKSHOP 7075 D2 Bronze &8| Brass M2 Tungsten Molybdenum High Speed Steel with excellent toughness and cutting properties. This standard grade has a wide variety of uses tools, cold worktools, etc. including drills, taps, broaches, milling millingjtoolstcold 414O 4140 Suitable for tor applications requiring high strength & good toughness, particularly in medium to large cross-sections, medium to high beflame stressed parts, can be flame or induction hardened or nitrided. For applications requiring high strength & toughness. Molybdenum addition prevents temper brittleness. General engineering, automotive & alrcraft aircraft applications, applitzations, can be flame, induction hardened or nitrided. PB 1 Bronze: Phosphor Bronze very good corrosion resistance good toughness used in gears, bearings and bushes. Brass: Free machining Brass used for repetition machining, high speed turning Sthreading. &threading. Bright Mild Steels shalting, can be case Cold finished mild steel for machined parts or shafting, hardened andweldsreadlly. and welds readily. Medium tensile steel for shafts and medium stressed parts, can be welded if precautions are taken. The addition of lead to this steel gives increased machinability, without marked effect on the mechanical properties. For use in automatic and semi-automatic machines torrepetition for repetition parts. 1030 12L14 l ———- 'High Speed Steels 'High Hioh Tensile High 4340 Key Steel _ _.LCD L ĚDhi NJ FD_GH _LCBGrbCD CD UQ CD A 1010 -L CD CD -L A tully fully killed medium carbon steel, suitable for medium stressed parts in machinery & industrial tools. Can be flame or induction hardened. beflame Soft ductile, easily welded grade, case Main usage usage Qtilltildl general DUILUU ' IIU, tfidtilly WUIUUU gli:tUU, Udtitd hardenable. ll'ctlUt'JlldUlt'J. lVl'ctlll tabrication. fabrication. Pa-IL Juctlln In-H-1l....a.-.l-l.t...l -....-._l,_ ___L_.. |_.__l_l_ll_! _ . _ . . _ . ÂISI 01 AISI O1 Accurately ground round bar that is used for a variety of applications Oil/waterhardenable. such as shafts, pins, etc. Oil/water hardenable. H Silver Steel ~ . _ . _ .__l Stainless Steel improved machinability and resistance used to reduce machining i time, good weldability, can be case hardened. 303 3C3 I Case hardening chromium-nickel steel for applications requiring high tcugnness 8. ccre strength, particularly in large cross sections. Suitable for tor highly stressed parts, gearwheels & crankshafts. crankshafts. ¥.f\||r||i-\rn.n D nnrn n'l-rnnn-|-|-ta nnr+:n||||\r|\:.n|n1-run nu-Ann I-\l\l*|'::\|P|-\ LUUHIIIIUDD Ul L-Ul G DU UHQLH, pal Llbuldl |y ||| 304 f'||H-n|r\|n Cast Iron 358 35B Essentially a Pearlitic grain structure Grey Cast iron Iron with excellent wear resistance and good machinability. Used for tor Hydraulic & Pneumatic piston, end caps, support bearings, etc. eto. Chrome Bar 4140 ,AA hardened and tempered alloy steel grade suitable for highly stressed i mechanical - parts.i it A Suitable for plastic moulds and holder holderblocks blocks forthe plastic processing, die casting industries and components tor for general mechanical engineering. Can be case and flame hardened, gas nitrided and chromium plated. Case Hardening Steels EN-36A A MZOO M200 Carbon Hollow Bar 20MnV6 2BMnV6 ltit is manufactured to close tolerances and used extensively extensively' in the manutacture ot shatts. manufacture of keys tor for shafts. Plastic Mould Steel I Carbon Steel 1045 Dimensionally stable, high carbon, high chrome featuring excellent toughness can be air hardened or bath nitrided. Suitable tor for heavy duty cutting tools, blanking and punching tools. _ punchingtools. flnnnnr --==-. Copper A sulphur bearing copper for for use in automatic & semi-automatic tor repetition parts. machines forrepetition B14700 014700 Bronze: Leaded gunmetal Bronze, excellent machinability used in bushings, bearings, pump/valve bodies. Also available in Hollow Bar. 1020 _ Aluminium Strong alloy offering ofterlng excellent machinability for the manufacture manutacture of ot machine components and suitable for high speed repetition machining. This alloy offers excellent machinability combined with outstanding wear resistance &8. excellent polishability. LG 2 038510 638510 M IE!-t. _ld Work Steels Cold Li Description and Uses 2017A _ 4 Description and Uses Designation The following is a compilation of metals, commonly used in day-to-day engineering applications. its metal's properties and Its aim is to provide a basic knowledge of the metal's general uses. it is always advisable to seek detailed from the metal supplier. deiaiied information irom suppiier. Designation A COMMON WORKSHOP METALS couiuiou wonkslior |v|E1A|.s 31 6 liltiilltliil ill ll ll 31 BL Free cutting steel tor subiected to corrosion in mechanical for components subjected plantengineering, and plant engineering, mass produced items such as screws, bolts and bethermally nuts. Cannot be thermally hardened. General purpose austenitic stainless steel. Frequently used where welding without subsequent neat heat treatment is involved. he weiding invoived. Cannot be thermally thermally hardened. offering good corrosion resistance used in tood food Marine grade oftering processing, chemical, fishing, hospital and brewery equipment. Cannot 'bethermally ne thermally hardened. The same as 316 with improved weldability and machinability. Cannot bethermally hardened. NOTE: Reffer Fleter Workpiepe Workpiece Walla'. Material Comparison Comparison Table on pages pages 104407 104-107 tor , E: Tame on for Equivalent Equivalent l Nattonal Material Designation Numbers. National 7 ...-»._ * .1' at 1* '4 "*1, -"-.'-' 5 .1-'1. 1;", /*4 ¢.--141¢, . '.;'=:-22'-1-3-'1 - 104 1241 ' __ 7 COMMON 7 7 MATERIÅL WORKPIECE MATERIAL W COMPARISON CUIVIPÄRISUII TABLE TÄBLĚ I 150' usli 1ISOi U54 AISI/SAE MHLND. Mat. No. PI Steele DIN DIN France Standard BS ÅFNUR 1' BS. 1 nrnoa I 1|-I" LOW ALLOY STEELS 1.5710 36NiCr6 14NiCr1O 1.5732 14NiCr10 1.7218 25CrMo4 1 1.7220 34CrMo4 ´ 1.7225 42CrMo4 1.6582 35CrNiMo6 17015 150r3 1.7015 t5Cr3 E 1.7131 1 .7131 16MnCr5 1.0841 S152-3 St52-3 1.7033 340r4 34Cr4 1.7035 41014 41 Cr-t 55016 1 1.7176 55Cr3 1.8159 50CrV4 NlCrMo2-2 1.6523 21 NiCrMo2-2 1.0904 55517 55Si7 1.6511 36CrNiMo4 3135 3415 4130 4130 4137 4137 4140 4140 4340 4340 5015 5015 5115 5115 5120 5120 5132 5132 5140 5140 5155 5155 6150 8620 0955 9255 9840 . . . , L `040435 540435 1717cos 17170DS . . .. . . -_ ...:: 1 .- . -_-. &;.—,' »..::-.-.t-. -_ ./-; .-. -.-.-3 .~.,-2-~. .-*; -1 . ' ;- :5 ,4-3-1 __ , .- . _ . _ . _ . _ , 'r.-' 2'; >- 2' » -_ 1 4-J1 _-L IP . -7? S500 C/JCH O C) '11325 1325 1957 1912 1914 5 1914 i 1926 12912 2912 *STKM12Å 1311 STKM 12A 1311 1 2142 .Y105 1w20 1312 11312 1880

Stainless Steel, Titanium, Brass and Copper. ~ - \S SA 110. .\ '- its 3" 3’ A to I 1_5 1.5 I~ ågtgizigtztgizš 0or {§,1§orco app(pp if rfli$5, ifii qpygp fisooęaęezz >I~:*Z*§*Z*Z;§ 1:=:=:=:1:l:žz=z f:~:::«:-:~:«:«::~2;X~2;Z°:;1;:y' J31$1» 55 f1×××××> ‘O ‘C’ '$' iii’ . _ ’ 4 4 ~ -0- -Q & ‘O. -0 -I» 0 0_ fin"-'n»°4» --0-0» 4» a’~»"4\-’ S-0 ‘Q ~ O __ "0-0'¢an-0' Cylinder Cylipdef Shape - with/without End Cut I Cylinder Shape - Radius End ăĭm . Shape - Radius End Tree Shape I5 i ĹŕŽĬŠŕŠĬŠĬi:-_ -Q .-.-.-.~.~.».-.~, >°o'o*.°o'o' E$. »-.4°-:-:. .»:~:~.~.~:~.~.»,« 4+00&10 arecoapparecorQ55 0+0c ace0 -1'-:vi-v Egfg’; ASKS o Ar__ at22+!-~’ I -Q 911 :v:Q:ą:.:o:Q:Q:Q’ Q0 O V 32:2: 2' - . Shane - Pointed Poinfed End ; Tree Shape 3 I1 1I 1I 1I 1I 1I 1I _:. _ "___" ~~ 11+ -- -_- —— ~~- Standard Cut ("3 g-0- ‘ I 44001AAAAP _ `Double Cut/ Ibouble Cut / ’ Diagonal Chipbreaker S Cut Chipbreakef nnn 4s,ooo _ ,_ ran 5o,ooo s2,ooo_ p 35,000 ss,ooo 32,000 .15. _§]’I CD CD CID Vý3[16’V"W_§ 22,000 3/16" 7 _e_ 1174", y4y*jy_y_ 10, _ _ ’_ _ 3/8" 3/a" 12 ł 1/2" 4. 16 ` is/er 5/8" zo 3/4" y 25 17 71'*1" I. 4+ i - i 1/8" if 1/8" O3 :~:~:»:=:=:$:~:=: ;~ ~-: -tgigtgłgtgągizâ ‘a _* 0 .6 4- 4» *4» + ’ >-4»»-11-->~oo~ '> . _ .y _ ’ . ’ ’ I’:- 1/15" 1/16" _s ::c.— i Q I . 90° Cone Shape Size_Ž(_l- teadDian1eter)1 _Size (HBS_t1B.IS!tlSI_8 ĺlł :-t Q:«_ , (inch) * Standard lullShapes ll’ Iii ‘Ill {IIIn ’ I : cl:co ’-1-1 cc CID -c: ccccca. :D III cc 55:5cci ::ica. :1:eo Sil -3 eo S131 2:. .. 1:.-1.:1: CID Cl! 1: enco::_ co caC? 5: 58:Š ro ::ca. ::c: :U:5:Š IIII "Ti ‘c:::I eaU! Jr’<\„~ :D LED l'_J ["III|I' lull IIIIIII II III. III "I i " 60° Cone Shape 5U1 Q51 ‘¢"1"@-'$4@’¢' ’ 7’? 04- F The file design products repaired metal removal on nonof the flutes. freeing metal and eliminates clogging ofthe Uses: Aluminium, Plastics, Soft Copper, Rubber & Zinc Die Castings. "*~ A _*rię*ĭ' i*Agfipgt i" Aluminium Cut: Recommended for use on soft materials. A -0 , Inverted Cone Shape - 2 4 10° to 30° 2 14° to 28° Cone Shape - 4 Q’. :Q S - i - zr A ii’,iii yr-ii ,11 1:1 :-:~:»:2:2:»:-:~: $32 .-0 0or 0011 15+ c(pp-1or111’ -4»o _,,_" £1’ > Diamond Cut: Extremely good tool control producing powder-like chips and increased metal removal. The surfacefinish, however, will be slightly reduced. Uses: Heat-treated Steels, Fibre Glass, Nickel-Chrome Steel, etc. SteeI,etc. --4’E§§§iEiiliiE§§5i5i5 Adto 1 *1?/o(p 1r 5% r 1-_ ‘101. . 11*" _ - 4- 11111111’it/Mitt ~: -ß°:°°Z~ Ito ’%"§_ 0 15Q.l £- ’ Double Cut: Produces rapid stock removal in harder minimum tool chatter. This design eliminates materials with minimumtool loading of the flutes &the production of sharp sliverchips. ofthe ofsharp iron, Stainless Steel, Titanium, Brass & Uses: Steel, Cast Iron, Copper Copper. , ~ :’-"~’ ~"" is F’ >Ž’I $11 1111’ AI1!I 111! ~"-*1’ "R II I: :-I.B:Đ "< BURRS II l= II II (Ih TUNGSTEN -II: IZ IĐ IV! -II11 I: CARBIDE IDlbII EE I: I'l'I ROTARY UU,UUU Ñ 1 I F eo,ooo CD SD CD CID CD ~ 42,ooo 42,000 30,000 1 1 z_5.oop 25,000 22,ooo 22,1000 1o,ooo 19,000 18,000 1e,000 1s,ooo 16,000 14,000 14,ooo 25,000 2o,ooo V 22,ooo 20,000 22,po0 1e,ooo 1e,ooo 16,000 18,000 1s,ooo V _1s,000 1o,ooo 15,000 14,000 15,000 13,fiWi714,ooo 13,000 I 14,000 10,000 1o,ooo I 12,000 _ , Aluminium Cut V_ _ _ - I ii? 23,000 r 15,000 1 271007 112-) aooo C3 ii?ii? @z NOTE: The above speeds are recommended for Burrs with Standard Shank Lengths and should be reduced significantly for Burrs with extra long shanks. The recommended speeds are intended as a General Guide only for Steels Steels, Alloys and Non-ferrous metals. The Speed for Stainless Steel should be increased by approximately 25% forStainless 25%. important hhporteart lilote Note : Because of the high speeds involved, ihvolved, it is most important that approved alltimesto safety glasses be worn at all timesto avoid slivers from entering the eye. #41 _ SURFACE lik I: II '111hIID l'l1 COATINGS tb IDlb ::'I: IDfh B _ COATINGS SURFACE in I: IS '11IhID 11 (D I: ,JINGS IE '% Physical Vapour Ph srcal Va our Deposition De osition {PVD} PVD Chromium Nitride (CrNl (CrN1 processthat verytough A low-temperature process that produces very tough coatings with high lubricity for use on gummy materials, high temperature alloys, low-carbon steels, and stainless steels at lowto medium speeds. This is a PVD coating and is particularly suitable in non-ferrous applications where titanium based coatings are not successful. Itit has a surface hardness of approximately 80 Rc and has good corrosion and oxidation resistance. ItIt is mainly used formachining for machining Copper, Die-casting, Brass forgings. Brassforgings. Chemical Vapour Deposition (Ct!D1 (CVD) uiamonu Diamond Coating ItIt is an amorphous diamond coating with extremely low coefficient of friction and fortapping Aluminium alloys high hardness. This coating is specially recommended tortapping with high Silicon content. A high-temperature process that produces highly crater resistant coatings with a broad range of carbon good balance of toughness and wear resistance for use on aabroad and stainless steels at medium to high speeds. atmediumto -1CID C'! :§ El Vapour II:Iii -'I E: Medium:5Temperatura Chemical Deposition (MTCVD1 -l1 l if E: Tnrnnn IUIIIPU Q9 IIIII C: =5’ IED C5 “CI CD C: nnoiiinn l|\f!TI"\|n\ CID PLIOIIIUII ‘III I UI U1 Hard-Chromium Plating This E2 5-!3; cn is a medium-temperature process that produces tougher, slightly less wearresistant coatingsthan the traditional CVD process and is recommended for use on gummy materials, ductile irons and high temperature alloys at medium speeds. The tool is plated with Chromium to improve wearcharacteristics and reduce sliding resistance forcoldforms. ItItisis especially suitable when tapping Structural grade steels, Copper, Brass, OLUUIO, UU[J]JUl, LJI GOO, etc. ULU. c\+nn|c\ Blackenlng Blackening n+n Nitriding Nitriding is a process that is used to increase the hardness and wear resistance of the surface of a tool. Itit is particularly suitable for taps that are used on abrasive materials such as castings, bakelite, etc. Blackening is a finishing operation that chemically coats the surface of ferrous metals. Besides enhancing the appearance of the components, the black deposit holds a sealant, usually oil, into the pores of the black oxide coating, where it is held in close contact with the metal and prevents corrosion. There are three types of blackening: 1. Copper/Selenium Blackening - This process uses a room temperature acid Steam Tempering Steam tempering reduces sliding resistance, thus preventing cold welding, which occurs for example during the machining of Steels that have a low carbon content. Steam tempered tools are mainly used for machining offerrous of ferrous materials. hsrth tn fnfnrm hlarlz nnnnnr rnnnar QP|Pl’lilllTl cnlnniiim rnatinn r-nntinn in nnnrnximatnltri annrnvimatelx/1-.R’74 minutes hath fnrm sist hlarir mini than I-JI-4l..|| LU tun IlI MHIMUII Uvrlrdvl vvl\i|||I-l||| \i\Ib\\lllU nu \-\rrr.1|v\\|o||.v’|J I -iv llllluv-univ- z.2. Caustic čšiščeš¡; `,"t' }ià1řrB"-"Ąbąfiši šęąšítâi ębšiširššéâèàuł 12ić1`ëć"ršF5i ř„„eS BlackàOxiding - A causticšą soda bathñ operating at about 140°C produces the surface oftheferrous metal. a black coating on onthe Oxylate Coating - Itlt provides a high quality black corrosion resistant 3. Black Dyed Uxylate rna ti n n on nnfferrous nrrn lie metals mntnle without wifhnufi Ici'nn heated hnsrfnrf chemicals. rhnmirzle A nrm/fnrrnlie nvtrlafn coating uvozu-15 vu W. ive... trrvtuw "„.„.„.„ using vuŕtza rrvctwt. »„„„.„.„„~. 1A1 grey giv, ferrous .\.„ł\„.~ oxylate w\|~.w coating is applied to the steel and it is then dyed black. This process operates ai at roomtemperature room temperature. The performance of any black coating is gauged by its porosity and ability to absorb a subsequent coating of oil and resin as a rust barrier. ittlt is extensively extensively used to coat Tungsten Carbide tool holders, Boring bars and Milling cutters to enhance appearance ofthetool. Titanium Aluminium Nitride (TiAINt NitridejTiAlN1 Tilt and This coating is applied by the PVD process and has a higher hardness than TiN TiCN. A very thin film of Al,0, Al,O, (Aluminium Oxide) is formed on the surface of the thetool TiAlN which gently increases the service life of the tool which can withstand higher temperatures especially when machining Cast iron and tough steels. Carbonitride -TiCNite(TiCN1 Titanium Carbonitride-TiCNite (TiCN1 TiCNite coated tools have higher hardness of approximately 90 Rc. TiCN is harder than other coating materials, hence cutting speeds similar to carbide tools can be achieved with the toughness of high-speed-steel. This coating is recommended for use in all all steels, cast iron and aluminium. Blue Finish Blue Finish is aathin thin layer of iron Iron Oxide produced by a carefully controlled steam tempering process. This produces a very thin oxide layer which acts as a lubricant and anti-weld surface. Itlt also increases resistance to corrosion and enables the surface of atool to absorb lubricant in machining operations. Titanium Nitride -TlNite - TiNite (TiN) (TiN[A gold coloured film of Titanium Nitride with a hardness of approximately 85 Rc Ftc is deposited on thetool which extends tool life by reducing friction and enables thetool to be operated at higher speeds and feeds. ItIt is suitable for machining iron-based materials, die-casting and plastic mould tooling. Other applications include wear parts, medical and dental instruments, slitting knives. knives, plastic die moulds. moulds, carbide tools, and high performancetorming performaceforming tools. Bronze Finish The Bronze Finish is a thin oxide layer formed on the tool surface and is applied on High Speed Cobalt Steels. Chromium Carbide (CrC1 (CrCl A superhard coating > HRC 80 is applied to the surface using PVD coating process. The hardness of the coating is the same as TiN but with an oxidation resistance that is 20to 2010 30% higher. Recommencledfor Recommended for machining Titanium and Aluminium alloys. pnnnnr Dr-nr\r~ l1tl1 ti1lfl11 1tli1 li1 Zirconium Nitride (ZIN) (ZrN) It is a ceramic coating applied by the PVD process. Especially recommended for tapping Aluminium and Aluminium alloys. :1 1; .. - g _ . -:.. _ _____ . _ Z RE Il iI Al 2 o :i iI:-.3.-4 §i lil + I'\l_-:-- --I m Polycrystalline Cubic Boron Nitride (PCBN) Ceramics - f .| It 1 as ' R I ' I LIZIIDIIIBS Carbides i i Cost/Produutivity Cost/Productivitii Atlvantages .A.t!\.@"i3it€$ iowScrew-machine and other lowcuts. V speed operations, interrupted cuts, low-horsepower machining. _ Priced lower lowerthan than carbide; gives longer tool life, better surface finish. Finishing operations on irons, steels. stainless steels and aluminium alloys. Ceramics Ceramics High hardness. hardness. _High Hardened work materials in Provides many times the edge 45-70 Rockwell C range 45-T0 life of carbide eliminates tor costly alternative need for grinding operations. Better than 30 times the tool life of oi carbide, carbide. even Carbide inserts toughness. Carhidelnserts toughness. Carbide tools. Carbide sale Ln Incexaele. Diamond Inserts *7, igDiamond*lfiiserts* -.. K-QIIIJ lll\.l\JI\.\.A|.JILb finishing operations Roughing & finishing on abrasive non-ferrous non-iierreue or materials. non-metallic materiais. . H C TiC & TaC is added for Improving heat improving and crater resistance. ~ f a *1. i Medium speed i l i i Transiierslb Youno’s Thermal H M" lnānsrerset Young's ' ił " ' ' ‘" i T’ iso 5l ISO lame Grada ttitaritness a "ass Rupture up me tŠ Modulu: ooniluotivity Moduius I conductivity cim lCla'ss} (mm) A (NRA) l Zifil-Z'>"\\"".'.'.-_ ‘Z ’ . - ';."'"_-';1"'§_"')'!l"'~£'i i . ;;\-.a'_:t.;.;-;-_ \°;»;*-,/".e-'~.-§'~.".>':1l P ¢ ' . §¢.'j.'=')'-., t:-Y ' 1 . >2 =;»w/;'._;j-;'!)f»-,y i ->'>.,~'-Q .. .. . an ,_., l I- Wu, .=:5~'r-.:;.,.-.'.g.¢-p~~~ __.__-..-- r__~~- P10 =.=:a..;?: gt . —"f',:,~¢.~;-.1 i 92.7 92.7 strength 5 (tour/nim=) , , (cal/cm Strength (kg¡mm,) 5lllllltq/mm) (oal/cni.xel:.K)i . sec. K] l (Ii(kg/mm) g/_mI'lt,-I (kg/mm’) I J > 200 Pz" 92.5 925 i >210 . I 5 Comnressiiiei Thermal 10ompressiveiTh°"".a| strength iemapsj Ę*X"a"s'"" I stieiigth I .|..... Šs$` 53 i i II I i1 ii i 0.07 i iIlI i coeflici Bil! imnieiem hu /,m (10,/,0) «I 460 A 480 l _____.._.’,___-...,,_.-_-_.____ „_ ... 6.5 .4- "W; _¢:.>.:: ;'.;~1_¢_ .,_ 1 Roughlng to finishing finishlng operations Roughing on aluminium aiuminium and other soft or abrasive non-ferrous or non»me'tallic materials. non-metallic ' Machining speeds up rn/min and beyond. to 1500 m./min T'I >< ceptional hardness. i I'Exceptional Polycrystalline Polycrystalline- Hardness Hardness ofol diamond diamond Uiilmonti-Tippfltiy üiamond-Tipped. plus pius carbide 5 PHYSICAI. PHYSIOAL 8: & MECHANICAL MECHI-\NIGÅL PROPERTIES conventional life of conventional Carbide grades. Cubic Cllblü Boron B0l'0ll JYI ,\l\1IIIIIY lilll 20 times the tool Up to 2O Nitride NiIl'itIB 1 Pgiunrueiallinn- ' mili-roli resurfacing, finishing tinishing Better finishes at higher Steel mill-roll operations on cast irons & steels. machining rates. l_. _.....'..1 Silicon NiIl'i[IB Nitride High hardness hardnessp/us Floughing and finishing linlshing $i|iCOIl plus high Roughing irons fracture toughness and operations on cast irons. z. thermal shock resistance. i Features šüompositionl ,Compositioni ' 1 t .._ ii _ Excellent resistance to heat, wear. shock and heat. i '*~ +. I , mio -;——> -r_> gpplications and Productivity Advantages Agplications Cermel TiC/TiN Cermet |12s lIêí Less TiC & TaC WC + Co +; + is added. Better shockk TiC ++TaC TaC ti wear and shoc Turning ! Stainless Turning resistance. Mmm resistance, but M _-..'lvliiiing M20 Steel steel ivizu 9 _ i less heat and Heavy cutting i crater resistance at Low speed M40 i than P grades. c Tc. finishing 1 Cast iron I Finishing No TiC or TaC. Hardened t steel Turning Medium spee iTurning speedd . i Excellent iWC WC + Co i mechanical wear .K20 Non-ferrousi Milling i resistance and metal Reaming _ iReaming shock resistance. '^" Noni "'ĹóQ;n}Hj'lÎnš"'" Low-medium K30 Metallics Metallica i 2.speed speed Eiii r_i__.__.____ii___ . 1 1 M10 M10 Ultra-line Grain | Coated HSS Powder HSS ' material than carbide. 'iie. i -, HAÅRIDNESS HSS _ 1 - -:5-'.:; :1.'"._~,/~."'" ,\'iI Coated Coaled Carbides ' APPLICATION ÅPPLICÅTION -' - ' '?-.-'-fr"-'>.'~}i ,.....__.__.... '..2v.._-_-~Q~ -~'-' ':'Ir.f>'*' ·i'-:5.-~,;=\ ""€*~ '-:-.iY§;'":-.t'-f~.~t . ..._ General Cutting i at Hardness Hardness Rockwell A scale Hardness Rockwell B scale Hardness_Rockwell Hardness Rockwell C scale Hardness Rockwell D scale scaleee or ININ PL 1 INSUL insüí I T' _J Hexagon head Hydraulic inch Insulated Insulated or insulation _ I Radius f Revolutions get per minute Right hand e g BM Round head ___ I so STD SHL_ sviie swe THD ren TP1 TPI vot.. vol WT _, Spherical HTB Square S_c_lu g St_agdaro_ 5ifl"EI_€1_tQ... II I _ Z _ Term Term c P ' © I Ii U Ñ Difference Different; I Therefore Tim iI7o < l E __ @He S I Pi _I Parallel To IInerpenoiĉoiarro Pg_rngi1djgiiI3_r"TQ I IsIS To Iiąatio) (Ratio) T' I _ I" Ž I'l _ — Anoulariiv ADQUIHTIW 1 H"? Arc` MIDI" tengr Il ' . .. * max. material condition At max. material C0l'ldl'[lOlIW _J At l_east least material condition I Basic dimensions CU paE3. ca E3: E3 ct: -:iIDIUI ID Q. I Circular runout II Circularity Circulaiity COHICHI taner ĺalifif |`_ Conical r' l Contricity/Coaxiality Counterbore/Spotface COUTIIGYUOYG/SPOTIGCG 1 Countersink Cylindricity CYIIDUFICIIY |_ Al ll ET 7 T l\'lrr\ ___ Datum ISHIUTB feature -I DEIIUITT Target Dflĺlumlfĺfgfli Ž @ I Datum DIHITICIBT ñ_ IDiameter I Dimension not to scale E _jicsa li ga 47;; __ ,Ĺ ii', IDimension origin rvimensvn origin ti-'I-t'§"*]_-'"'5-P"-".=.' I . H'Il synioot Symbol :Term Irernt ' T __ T kr I A7..- 'f _ Engineering Drawing Symbols ,9 I A" "Fund " /9 _ĺLÅII FOUHU - _DFOTIIB Df0ffl9_t _ or L VT SUITI Of -—Sum I Product Of _l_ I $lll11I10I Svmiwi ITBTID Iferm 4 _ Proportional To 'I Depth/Deco 'd _I_ DŠPIII/DĚBP __ I Infinity".Infinity oc OC \ H ll— QI A 'Standard Standard (imperial) (Imperial) wire gaugi gauge f Thread 5 Thread per inch Volume = Square Root Ot Of W ', _ -\II \Y ,1__i I II I MI We I ill IQ I W 00 (I) Equal To 7EqualýTo Ž 2 M at H Not Equal To III L'? Approximately Equal To fi z iz I> A ~ Of the Order Of/ Similar To Greater Than >ý 'GreaterThan Greater Than or or Equal Equal To 2 < If I Less Than or Equal To 3 nivioeti By Divided [Q __ |y|a||ıęm¡t¡i¡;i| Symbols 3!m|¡0|s Mathematical Term IIH $ymIJr;ıl! syrnnni *rerni I`_ Minus MIUUS or 01' Negative Nfliilative or Pos./Neg; Plls/Minus Pos./Neg_" i t _ I Plus/Minus _ I Multiply By _____X By_ X ___IVlultlply I A _,_.,_.,_.-_-_,_r x;_ It -1 =1 -1 '.;.;= 1; I Plus or Positive "If \Bee I \ _ i _ 'L'\.@.|_me_ —' ‘ __ Weight E swear , SYDTIJOI Symbol +t I co Igg __ SCR Screwed __SCR___ H I Second (of (oi angle) anale) SK Sketc Sketch SPEC ___ Sp_ecili_c Specification SPEEL @wi _Z sen SPH Hardness Rockwell E scale Hardness Brinell "rrv __ I Hardness HHTCIIIÐSS Vickers VIQLĚS H;HEXv_ g_ssa_ I Hexagon HEX HD HYD RPM EFI/L RH ni-I nn HD HD _RD i.f_ : 15;} , 3. mm", '11 1:::N ENGINEERING STANDARDS |"_:z E::111 If' EE:: rn DRAWINGS I:'Đ5: :E :: onon " ----------: trn FOR II Common Engineering Drawing Abbreviations Abbreviation Abhlĕvial ionII Term Term 1-"'":e :1; ri _ A V" . :'" -"'1-,' -'-"' ' c - . e ii s- " >.'-'i'$" - ' >#"'S :1 E-1.'.: I á>L@AB C_I Feature control frame ==@@5%@ABIC' I A Le Z @mess E Flatness I I _/X /X _ y Number of times/places 'I _* — y //-r 7 I"Parallelism Parallelism i- I1 Perpendicularity I Position I"U5|L.IUI| Q9 Profile of a line wmemame I Profile of a surface Drninn+ IProtected IUJUL'l co C2. tolerance i i iiCID no:5 cuci: r~.zone i ş> E @ Ž II I Radius I I Ž I (40) IAI 'Reference Reference dimensions dimensioí u IX Qt ‘ Slope Lope ıi SQI ISpherical Ž Spherical diameterý A SO diameter sa =I Spherical radius SR U _ (Shape) Square (shape) — I IN ~ square ? Z I Straightness Straightness i Symmgtfy ii Igymmem, ' T >< iI Target poim ý>< point iz I ~ * _ __ .. 74- ___ . I M I"'\ . .'¡;!.. __M M — J D>ee D I1l'\ -1 Žszo _ _yt " /y ft a ‘T5 -*1 -.'" _ Irotairnngnt Totalrunout _'<.'.<'.:.' .-=_II-~.'_i=:.-"-.~~. "r=."§@ __ 144I M _____/_____ "77 Auuo PHYSICAL Pi-ivsir:AL niiviizusimis noun DIMENSIONS "_'"' ' " ' "wu _'m-"nn" . in . Adult Male Dimensions E [Of Small ogeralor ma percentile) 0 era percentile]___ (5th 19__A ' ž $15; Lerrreooer.ator @mmm je E I . I1 leee-NAAAI if A It _ _ Ē E - 5 °/0% 'Sew %ipI 50% 4 7 95 % * 7 I 100% II]II% PI" ¡ B G D _ ' H lit iIIii I i I I III" . _1\7i --:_ A A. - A will lireaowiotir F H. A_ I _ ' eyetoozot IIEyeloba'ck .. A. . .-_ ' I Chest depth .Ci1estdepth . ' K. Infiminaiiårtn 'AbtlDmin3IdB|]Ih »AA ' _ . . . . _____ . . I v L-4i——M u — I ti >< ___ 'U "§%V _l "'"-' Ir'I —$— r - | Q Y R :0 I T—I1 E5T ' IESTTIQ ěC I—c wm EE Z I'"'-I ; __ - L _-L 3.74" __ -- 3.74" I70 170 I 6.69" 6.69" 170 I70 I 210 210 210 A I 5.98" LID =-=2 A 36.50" 36.50" U'! PO ____ -L 4.13" I15 I 4.53" 4.13" 11541*. 4.53" _r __ sass" 72300 82.68" _I 2300 'I ooss" 90.55" A 7.40" 205 5 3.07 7.40" 205 T 5.07? 'I05 A 105 " I88 188 I 5.59" I88 6.69" 188 _ 7.40" 7.40" 8.27" 8.27" 245 9.65" 9.65" A 8.27" I10.04" 8.27" lI I 255 255 . 4" __ A, CD U1 165 . Q') 6.50" Cl'! =2 1016 40.00" ioiš II I4o.oo" $.71 _ ' 21oo 2100 .. . 29.53" 29.53" . .I I __ .I __ 31.50" 31.56" __ ? __ 9.84" _4 _&.| _ . . 205 205 I 8.07" 8,07" I 280 14.02" 280 11.02" IA 300 11.81" 300 11.81" Int ' 2e5 285 .. ; . 7 I 1 11f22" 12.so" 11.22" 1' 320 320 IA 12.5" ___ L 825 825 I32.48" I s2.4a" . . . I 880 734.55" . 34.65" Vaso 1. . ___ A __,.,.... _I.. i _ . .. ,... _ .. .. , _____ 15.75" I1 15.75" . " . I 900 35.43" 900 A 35.43" A _ . _960 II 37.80" 960 37.80" 840 1 33.07" 3407; 39.97" A ...__.... , _ __ 490 490 ' 19.29" 19.29" _L_ . ..|:s.C5'.: C3 . 120 120 II . . . . . .1 3 .1. U'.: U1 |-\3 _|. CD A -I. 4.72" 4.72" I45 7145 17o II 6.69" 6.59" IA 1tee 170 se eso 440 380 I 14.96" 14.96" 440 A 385 385 I 15.16" 15.16" 450 450 I 320 920 072.607* 355 I 12.eo" A ass _- . _ _L __|. 4. 19.69" » _st§i 500 AI 19.69" 560 722.05", A 22.05" 620 II 24.41" 24. -isQ25250 I __ I 16.54" 16.54" _.A..... _ I 17.52" 17.52" 445 470 470 20.47" I 18.50" _sâi Ĕo.47"7 I __ A 41o 1e.14" 460 I 18.11" 410 I 16.14" O0 _ci 1,1o _.1. Ĕ: I no5:: 2o.oa" ca 420 =; s= Thighthickness 71' ==.=== IHandlength _âhoulderwidlh I?' A ;?.ShoulderwidAth .- , IN I 95 400 I Back to call _EBaclrltocalf .....,_ IL A tL'trA Were-.~:,;e;~;f" "fi tiiiiiii ' >-.. I'Il 'I1 -u=I'Q A 27.17"Ž 27.17" 765 AI 30.12" 765 50.12" *. 2o.e7" 20.87" . 590 590 t 23.23" I sso o5o7I. 25.59" 25.591 I 200 zoo IIII7.s1"-'WI 2351 9.257 I z7o 270 SI 1o.es" .' 7 . 87 Łzas 10.63" ,. _ I -12.°= _š!"? 1. -I:Forearmtohand IForearm to hand Tool FL CJ1 U1 95 ; 750 800 U 1.F'=='.¢=A Aeteeeeeetgat MWlIišť ' ez v-4 . I 5.51" 7152 927 927 Eyeheighl 690 IzI;;r;r;r,n"7 on ASholiderheight 7" si 530 fiiaimtrarírа ¢_-..._ IKnee height height(with (Knee (with shoes) i= E- --1 I' 25o 250 M. IAnterior IAn_IIerio_rarmreach arm reach I Chest height height1I t K .~ fl'h. 'I1 CD '--v 1ooo AII 74.80" 1900 74.80" _____ . I Headlength IHeadlength I.».. X L r-i—i "°I°"'"°I° 837 e37 I 32.95" 32.95" IHorizontal sitting height II-IItJIrIZ0ntaISiI_Iing heiIgIII_ El I'—"i. Ifl M If I ai AD " A 1... 140 Shoewidth Isnoewiutir ___ . I E _-' ~—"'"ĉ'i-_ — __ Medium 770*-,Ĺ,:I'; I I I,Hee [I width . ___ . . . Iii. H/-if _____ tíšl ~. _v c. _(Overhead 'üverhead reach reach r ___ A 71-: : _ 4-I-I CH no=3' E. jHIip pointtofloorAI Ìninpointtntinnr J> >- E || °"°'"'I°'. Ii . _ _____i_ ... .i . _ . . . . i. _ . _ G ' , _____ i Large perator Operator Percent I (Seth tit Pareentiie) Percenti * .-E GI! 21:F Fercenitie) " Eerceniiie) -A a- _:II .z:r Percentiie) M A WEIM 'Ž I - "Weight A I I Wei hl AI I-.55-lrgs121.25llh's-J6.-5 216,05-ihsi .. - A- _.. A - . . itosA . ¢... 5- llts 15.5 kgs _:168.6_ 5lbs 1 68.65 lbs . '98 _l lB_llags. r_gs `_ij6_.0_5 llrs __ (inch (inch) (rnctt) _lg eš oh)I :i,ti=`-I (ITTCII) A IA T' 1550 '17-.--.. l 1/15 _.. 11 ti/.52" -- -.. l 1880 Il 74.02" I or.uz" _r. U1 U'I O G? I 02" 67.52" ieso I 74.02" __1715 1585 I 62.4 A 1585 62.40" 1750 68.90" 1921] 75.59" 0" 1 75o ' 68.90" 192o 75.59" - 1-in A S Small:.,,, 09"*-,' I Designation Designation I I AE I _ . D. ' G7 iw/___ l 'fie. Errirm éli_oriws rarer' ' eso 33.465",, A oso s7.£iIo'" '1o5FI Ann span, =pan,einow=toitieo s5o I 33.45" 950 I 37.40" 1o5o 41.111175 41.34" _J . - Symbo|.I Symbol.. . . Λ Ĉ'- I _* A Heighl 'J: ' E -F" =I" (with '- " CIU E. =I' shoes) U'=1'I: . __ 'IE _____ I Arrnenzn B.. IArm span — I r li II *r _ I L. fShoe IShoelength length it lg" noun PHYSIUÅIPHYSICAL DIMENSIONS ÅWI-T AAAAAAAA Page DIMENSIUNS AAAAAA (RBIET P3gB144) Ft >1 _____*i_____ I ' \-TC' $(-)cU 1 A I95th percentile) percentilel (95111 Mediuni lTeratot operator ivieuium A AA _A ___ , _ - _ - ~ ~ ' 'I ' " (50th percentile) , M> _ / (50thpercentilei ____.~~-\"" I' ' F___---"(AAA E; L.--.š_Uf "A N 3 S -A . _ A i . _ . _ . _ — 170 I 6.59" mi 67.51.-ifI 205 205 T a.o7" eo? A soo 119.59? 1 19.69" " I5oo 5.71" 5.71 " I 7.40" 7.40" I I 17.32" 17.32" II17.72" 17.72" _ 7.1 I 14.37" 1 43 I __ I... ' _ .. _ .. .. I _ . 515_ 1I 20.2 20.28" 515 _ B" __ 410 16.14" 410 I 16.14" ., __ Q Source: Data compiled from ISO 3411:1999 Human Physical Dimensions of Operators. A NOTE: The above information is intended as a general guide only and varies significantly throughout the basic design of workstations and equipment. the world. Itit is provided to help inninthe 0« The 50th percentile adult mate in the United States between 2S-65 mm (69.1 adultmaie 20-65 years old, is 1755 tnm (691 ") tall & weighs 78.4 kgs (172 (1 72 lbs). This equates to approx. 2-3% > than the figures figures in the above table. heightisis 1 650 mm (64.96") and for iorwomen I60.5"). ¢» The worldwide average male height inomthe is 11537 537 mm (6D.5"). ¢» Awheelchairuser's A wheelchairuser's eye level is approx. 370 mm (14.6") belowthatofthe standing person. e.^ Wtteeichair Wheelchair users need a minirnurn rnlnirnurri aisle aisie clearance of oi approx. SOO 800 mm (31.5") (31.5") and aaturning turning circlel' circle ofofoetween15oornrn(59"Iano17oornrn(o7"). between 1500 mm (5o") and 1700 mm (cm. A II thGI =E ADULT I: I: 5-1 I1_4l I Ifli c-coo: ADDRESSES-I' I" CONTROL 'rfi' en:: -t:ioc: ,.azUeaÑII5 tr:::I "H I'l'I'Ĕ si NUMERICAL ::QC:Uil USED IN Cl U! I'I'1 :I 2 EIĚ In:: EL' ID :zrw: 'U :E - A-(Mical Typical Furniture Measurements based on 50th Percentile Male Dimensions in mm [_ A II \ __.-_ ui \ II „„ Ž.I Denotes point to point rapid traverse operations and intended as a guide only. The data therein should not be assumed to be accurate equivalents. grade s maybe may be obsolete and are included for reference purposes. | Some grades ..~t.:. . G) It nn nnn .'"\LiOUUUi -Fa.C3OJ UPI CT) CD CA3 CD Cf) 42>. Tl -L C r. i nnnnn i l i 1 4 co22 0022 iHt3A iiiaA3 875 875 Ĺ C- I'|'l C") CD GJ U1 _,_ i iii-in l\tI N10U SV515 SV51 5 $ V03 I\J "T1 Xzo SV410 Toei s ;TD915 U -I-5.CD C3 :-I organ i .-Fa.U'! I i Tooos Ti sno0 .TD905 T150 i l i 0028 veze 0028. V029 Ei5ŠvJ= _ T. . _ _ xerss A I'1iU NP32 G1F z 890 seo smo i ete I010 1 $ VC29 i vc29 icio . K313 Kais HTHOTi co2s; HM Ì`fl10T 0023 l l N30 EN510 K10 T H10T Him ' ` His isnsio I020 iczo 5 xsa Kes inteoroi V03 Hio i vos li E °, ` ooze 0028 i Hi0 2ZNwAQ ; l N21 TH1 Hx H1 H1 THT c HX l K6 | i H1P KMF NP45 890 Gi OE NP4s 690 GtOE Q.NT. |09015 l A30 Ĉlqzl'ĺ 1 °_____ VC28 i V028 ASUN A30N 2 Z _i CT 2ao N40 M20 A30 i 370 N016 V0111 VC29 V029 FI'I flnflb 0 -U 'ii F _...J I . _L LTI H1 OF H10F VC35M V035M G3 (D C3 i i U2 uz nx i HX l EH20 H20 me H13A iiisA V05 VC5 l. P30 ' UX30 IIII é "U 8- :- się.-zj 5 i mam, TD90i 5 SV51 5 "I-7" TD9015 GC4025 TP2000 UE6010 l0804t3 l08048 T9025 SV41 5 G04015 TP1000 A02000 TT250 TT25000 reo25 TPtĚOO ACZOOO JC215V GM20 169015 K09025 K C9025l 1N. o JC215V P20 UE6020 |09015 roots TD915 x SV525 KC 5050; GM25 K08050 601025 TP200 GC1025 TP200 J05015 JC5D15 __" 1 - i-an rrirrrflrrfl ---i- I 7774JC215Vi ih r--4 tPsooo' "teaser T9025 SV525 ` Teeooo K09040 JC215V i GM8035 GMBO35 K 4 1 UE6025 604035 i 109025 |C9025 690 0,uEso251cc4o3s T9035 SV330 moon A0000JC215V ,3 TP2000 50 rsoss JC325V CY250 CV50 ('3328 K05025 KC50251 p30 ' JC325V IC328 US7351G05025~ i US735 G05025l 72c::-i—5 T0930 SV 23 TD930 SV230 Kceso i T2sM ` K0850 T25M HC844 JC5015 H0844 .2 SV 23 5 SV235 T4oo 3 lC635 GX30 |C635 Ê2_2IĚ-I T9035 i Z mw%m: .. U9OM CY30M N52 CD »..- -. , 8 . 5 i ., i ézzflgb łts II//lg-4laV fits"/If ufliwu Z4 zahggqgV S'4¡¡Dl/k ~52 s 44 .6.0/ii.. Teoos i sv4os "l'P1000 AC700G` iTPfD0O Acrooei T9005 SV405 JC1 1 UV GM10 J0110V KC9i0 UE8005 GC4015; il"l'1300 lC428 |\) ?? so 0 0910 UE6005 604015; TT1 C'}4; co ___ any CMPv A01000' A01000 Toeos i 3V305 svsos yi Qi -4:2 J05003 H05000 uoouuoi i`l'P1000 GM8015 K 09010 i UE6005 onsets 'kceoio uesoos ireiooo roeoi 5 i SV510 TD9015 SV51 0 JC100V GM lC90i 5 Va.»l-;'é'4,¡¡,¡4ME f-4927m. 2 _ .M/rsl405312 . GM20 i K0990 `UE6010 UE6010 604015lTP100'A07006 G04015 TPiU0]A0700GŠ 20 l0fl048 lC8048' 1 ; KC935 iUEG02l] iA02000 GMB020 iGM8020 K0935 UE6020 GC1525 601525 TP15 §A02000 J05003 lC570 J05003l I0570 cP2oo KC5010SUCE010 6M10 iK05010 UC60i0 cP2o0'i\ GMl0 I'I'I I _ I. Z isacsg z...:y iIj,,/ 'C10 K10 teaser"_ __R 43aa3-~ yrs »`41__ i i :.>:~:'~:Ĕ *Š ;¡t;;.~... as %%fi%5 au%%§ sauna N55 I ifioafie" ;'-L ii; i. 5.;5: .4' ST30E $25M S25M ii S35M I K2Š ` "~:~'-"tram: 1- A30 Å30 sea 883 K21 , íífiý |028 I028 370 I/5,8 ‘Kuhn /.g-4.48 flłufl/_ Zf

G75- G79 G75-G79 Unassigned. G03 Circular interpolation -- counterclockwise movement. G04 Dwell -- a programmed time delay. G05 Unassigned. GD6 Parabolic interpolation. G07 Used for programming with cylindrical diameter values. *_-Inna III . .1 O (D A -I?»W Ln ii “1—U'l—I [ZED Ii —” “ML _ I _L -I "TI A A 1 I 4:I>5 ;,’L__ ~ -5-rii '11ov 'J coca Z III? 8I53$° EQ lI\:1 I ~_ G64-G69 G64- G69 I Unassigned. I I l G81 GB1 GB2 C’)inre G09 Programmed deceleration. G83 G10-G12 Unassigned. (504 G84 G13-G15 Axis selection. X-Y plane selection. G19 Y-Z plane selection. G20-G32 Unassigned. 633 Thread cutting, constant lead. G34 lead. Thread cutting, increasing lead G35 cutting. decreasing lead. Thread cutting, G36-G39 ` Unassigned. L-v——560——-1 G40 fi*-ÅT ~=-tr liši 95’ 1095 O /_\‘//IE\—I A I I , \7< IÅW fie? I 765 7Is I ÅŽIzë>~å)Is\åsII . - . ’ –:,~,-’- I;-’- 9% . “—-. .- -,-.- - r ,1-;. 1’ :.]. =1.” =-.< r .- .-. >..\..-_.’ .~ 1 .’,.. _. -.3 ‘._- r’ _-,- ¢-. - -3’-~ -. -,:Is_ ,. ’. .”* MlI Il IlIi II II iIl 7 Cancels fixed cycle. ocyle. GBO G80 Programmed acceleration. acceleraiion. I ’ ‘.e.’:». : ':-I ,» - G63 G08 G11 .--"' ,"' _ 1.” ne __ I I -G63 I TappingPmode. G00 sq 1905 I- Description I G-Code I Descrl tion Description G-Code Descirioiri Drill cycle. l I l l 1 1n 21. -; SE cycle. Drill &§?° 1:dwell -: l i ED :2. CU UIUI Peck drill cycle. Tapping cycle. I G85 spindie Boring cycle - rotating spindle retraction. G86 Boring cycle - rapid traverse. G87 GB7 Boring cycle - manual retraction. G88 Boring cycle - dwell & manual retraction. G90 Absolute input programming. G91 GD {ID _.L incrementai input programming. incremental Preload of registers. G92 Cancel compensation/offset. ‘-. G93 lnverse Inverse time feed rate. I G41 comperisation left. Cutter compensation G42 Cutter compensation right. G43 Cutter offset, inside corner. C’)4:-I; G? ili .|.:-. CT co Ë:1:: £1co ::i:co -’T-I G45-G49 Unassigned. G96 G95 Constant surface retraction speed speed. G50-G59 Reserved for adaptive control. G97 Spindle speed programmed in rpm rpm. G60-G62 Unassigned. G98-99 G98 -99 Unassigned. et, outside CD 331CO Feed rate in inches or millimetres per minute. G94 G95 corner corner. l i i Feed rate given directly in inches nr Ar'Ar'gIIIAIrl"|DI'l'DQ nor revolution. l'D\.'t'1I|I'IIQ['|_ or millimetres per \]l it r llLJL\|\-I IJUI l\lI\ll\J '7 V V wY ‘ nil mi — . JIIII “LETTER LETTE ADDRESSES DDHE USED CONTROL E :INUMERICAL C U G IN Cl Š ãi E! Cl ,ElÊ siili:I: -IIlCD „. _ I'I ‘M7 Letter Laue’ Address I Š M00 MIJIJ Angular dimension about the X-axis, measured in decimal parts of a degree Axis nomenclature B Angular dimension about the Y-axis, measured in decimal parts of a degree Axis nomenclature C Angular dimension about the Z-axis, measured in decimal parts of a degree Axis nomenclature D . Angular dimension about a special axis, or third feed j function, or tool function for selection of tool compensation Axis nomenclature E 1 Angular dimension about a special axis or second feed function Axis nomenclature F l Feed word (code) G i Preparatory word (code) H M01 M02 l M05 M06 E5c:an M07 M08 M09 M10 M11 M12 J or thread lead parallel to the Y-axis interpolation parameter orthread Circular lerpolat interpolation tion itK 5 interpolation interpoiation parameter or thread lead ieao parallel to the Z-axis Circular interpolation and threading Unassigned 5 Miscellaneous or auxiliary function Miscellaneous tunctions functions N Sequence number Sequence number 0O Sequence number tor secondary head only Sequence number Third rapid-traverse dimension or tertiary-motion dimension Axis nomenclature , parallel to xX l QU l Second rapid-traverse dimension or tertiary-motion dimension parallel to Y Axis nomenclature R y First rapid-traverse dimension or tertiary-motion dimension 1 parallel to Z or radius for constant surface-speed calculation Axis nomenclature S Spindle-speed function i Spindlespeed T Tool function Spindle-speed Tool function U lr Secondary-motion dimension parallel to X Axis nomenc ature nomenclature itV l Secondary-motion dimension parallel to Y Axis nomenclature nomenc ature W U3 econdary-motion dimension parallel to Z t Secondary-motion Axis nomenclature nomenc ature X \ Primary X-motion dimension Axis nomenclature nomenc ature Y Primary Y-motion dimension Axis nomenclature nomenc ature Z1 él Primary Z-motion dimension Axis nomenc ature nomenclature til ti tli tl il il ti ti @ "% DBSOflpfi0n Description Automatically stops the machine. The operator must push a button to continue of the program. with the remainder remainderof An optional stop acted upon only when the operator has previously slgnaled signaled for this command by pushing a button. On sensing the Mot M01 code, the machine stops automatically. At the completion of the machining operation, this end-of-program code stops the machine when all commands in the block are executed. May include rewindingthetape. Starts spindle rotation in a clockwise direction — - when viewed from the spindle face. — when viewed from the Starts spindle rotation in a counterclockwise direction spindleface. spindlefaoe. Stopsthe Stops the spindle. spindle, Pn GS m r~l-pnnn nf tnnl hilt rinnc: pint r~n_rnrfl1_l=\vuuv cnirlgijgp UU §3 cs automatic :3at;If'UUIM HUU \]\.\.| but nu does uuuu not \]' coverthe vv u CD :3 c: E51. or Commands manual change of tool selection -1 cr Z ifwithiththei-words. st E1 H::r’ool,'aas 5.is possible ossiEB oftool, the T-words. O’) Unassigned Circular interpolation and threading P M04 Preparatory words A Interpolation interpolation parameter or thread lead parallel to the X-axis L M03 Feed words I M MISCELLANEOUS FUNCTION MISGELLÅNEOU NCTIU worms RDS usen IN NUMERICAL cournot Š n-Efr:= UŠEÊ iii Ñii ' I- rici ' z: -|::ici ,. . Code Refers to . _ A l ' Description 7 — ‘U Turns flood coolant on. Turnsflood coolanton. Turnsmistcoolanton. Turns mistcoolanton. Turns coolantoff. coolant oil. Applies to auto-clamping of the machine slides, Workpiece, Appliesto ofthe workpiece, fixture spindle, etc. Unclamping code. An inhibiting code used to synchronize multiple sets of axes, such as a four-axis lathe iathe having two independently operated heads (turrets). Simultaneously activates Clockwise spindle motion and coolant flow in the same M13 command. Simultaneously activates Counterclockwise spindle motion and coolant flow in M14 the seme same command. feed motion in eitherthe either the + (Mi 5) or-(Mi 6) direction. Rapid traverse of oifeed (M15) or-(M16) M15l0 M15 M15to M16 Unassigned. M17lo M18 M17to Causes the spindleto spindle to stop at ataa predetermined angular position. M19 Permanently unassigned. M2l]to M29 ivi2tlio An end-of-tape code similarto M02, but M30 will also rewind the tape; also may M3U M30 automatically to a second tape reader switch automaticallyto reader. M31 known as interlock bypass fortemporarily iortemporarily circumventing a normally i A command provided interlock. Unassigned. M32 to M39 Used to signal gearchanges gear changes if required atthe machine; otherwise, unassigned. M40 to M4fi M46 Continues program execution from the start of the program unless inhibited by M47 inieriock signal. an lrlleriock Cancels M49. M43 M48 teed override and returns the parametar parameter to the M49 Deactivates a manual spindle or feed programmed value. liilbll Mb I Unassigned. IVÎÐU I0 ID Mb! Cancels M59. M53 Nl5B use when M59 is initiated. Holdsthe rpm constant atthe value in usewhen M59 Unassigned. M6010 M60 to M89 for use by the machine operator operator. Reserved foruse M90 to M99 V \ El Pi' SURFACE SURFÅCE ROUGHNESS 8: & CONVERSION GUNVERSIDN TABLES SURFACE FINISH SURFÅCE FINISH EXPECTED EXPEGTED FROM FRUM VARIOUS MANUFACTURING PROCESSES VÅRIDÊS ¡iÊ¡¡\N¡¡FÅĈTi¡RiNÊ PRÖËÊŠŠÊS _1fl Rgug|'||1e$3Ni|_ Roughness No. N12 N11 N10 N9 iiiiciom ‘ " eters Ll Rarfi) Fiailiii'i) ~ . _ 50 25 12.5 6.3 R/llcrrumeters su zs sa Ra - Average roughness oi of centerline Fl ato : . /A i /"rw l -1.—P - - %V nofagn'f'c not =ememagn`f` caton r"\ \-j D'D`*reccttˈto prof _.'A lifit-\ nnnn innn 1-*.|~u'\ irirblutiibiluh l1d(_Luil}·zi.ruu ruuu auu Ifviiülüiñüüiñã Hã(_uiii)2üüfi iñüü ãüii Recorded direction diregtion y..'f!?!!!" . \ I I J?Q _I. D'"_onreectct'o prof profe i L Il (Measuring length) Rz - Average roughness at 10 points - A -P 'Wm_ y - E a H ‘ magn`fcaton f'cmagn at'on '4.-i Ñ H? 2 Ln WY .: =cfonof -of Ê*~ i~ fon c D'"re prof 7:1 m R3 r- ‘ _ ? Ñ /M . g' . convefsion Tables Tables Conversion Average iM` aximum Average Maximum Roughness height . h 5 ofcente rlineg_____g_____ Z 0f fifflflflflifls_ Ra (um) _ Ra (pin) Ry. (um) W|1fl(l.1i'l'l) R\l'(_Lll11) N iu* 0-012 0.012 i.....Q-.59 „150 . 9-95 0,05 . N1 oozs 9% 0.1 to 0.025 1 0.1 _l|..1. N? NaN3 —— 1 _ —— 2 _ -._____ . N4 N4 N5 _§ N5 N_fi ill? N? N? 5 NB H5. N9 i ..J_9 N1_0 N1_U__ N11 “ PR *N11 25 N12 77* fiN12 Mi W *so 501* 1000 1.000 zooo .2000 - 1. 00 199 200 A T Wzoo 1. 00 1.9.9. 200 200 i. ; . 5 _g_ . . . ` V Å W .-. 1.1.’;-: . .:; . ‘r.-’11’1-.’ Il i lit iltil i til il — l i U U ` :2’-I2-T-L1: ‘.5:-§\l-l'T_I K il __ , _, . l ’ ‘ | y ii X- at-I 3131'; l i. _i W 1 -_____i a_ai-_ -I-lęfl mzPr—4aa=nm; ‘F|l' ‘ i \ I siT i i i it r ' -1 ' i I ' 4 " ii' 0 _(I I I A A . . __ ti _L E ll m::.1=-—=-:|n:I>=-šE; l A » . I A .. ';:5;=;::_;:.¢j:.'.-,-;_.-. l `) C _»T A ((i_ errtcl„„ fjf .I _Ž; ~ A _ -;-;~. '-}.'.'-!-:-'-.'7:'-'.-T1-2I1'ˈi-";'!; 1;: U H __ l” Extruding |__i_.---._.. Drawing/Cold Rolling Rolling" g Die Casting W -t W A b Z l as l | t investment Casting ('"vs$toet1..9eeiitL VW _ _ _ l l l __ Ziri FTTiirfliiiiirliriiiciéiaiifi. grm-Mwflflišfý y{__ l VV __ Forging VVV 1 V L .$.*.'1l .°?lâ' iF!.@1___ I . 03 C ` _ __„_ _ WH ‘ .- :-;'.-.¢.-:- ` A 5051* l »Ž V; l l _-i_-¢l_'-».1 I Sand Casting " ‘ T" """""“—"" Hot Blliiiflg Rolling M Hill | (\ l l I Fir" “"""|"""""" ‘l"i 7 F*‘ *V l .. Super Finishing Y Z A -- Polishing f_0|¡S|1¡_I19 |_app¡„g I-aiiiiino VVVV _ fD \-Illkl \ l R0||e|'B|_||'|li$|1i|1g Tr'l range Triangle Symbol U u.oU l) l Honing Average Average roughness 3 at 10 points atiopnints Rz (pm) Rz(0.im) .0.0fis _ 9-.*.53_ - 31"' 211;-E1 .;;:- A :.; -r.'-:-_ ' Z~-.'?'I- iiser Cuttiiig I19 H g 1I g r_7 __ Barrel Finishing Finishing . . - 5 we. V LC \ _.1= _v" i=.r.i _-fl_ =i eri=.f g 0.125 0.125 0.05 0.2 0.250 0.250 005 A _ 0-2 nin 4 _g__ g 0.4.l>. 0.50 o.1.o_l o.2c on.h o.e 0.20 i 0.8 1.00 0.40 _____„_ _L 1.6 zoo 16 0.40 1-5 __-_... _2-.000.eo egg _ W/i.0 0.80 ` .- . 32 3.2 4.0 1.5 1.6 Ñ -'i 7.1 63 ; as 7.1. 3.2 § 12.5 125 12.5 12.5 .125--. . 12.5 6.3 250 25 25 S250 9 25 25 as 12.5% 12.5 500 50 __ M50 50 500 so _50 ——'——fi I __ , _suriazeoriiñãng ghz . A -.$.tr*ats.w.-·-. R7 g ‘I ÊI ‘!§1 zzl' W LEI Recorded % ÉL l .- - r. -. . „.v v. 1;” v-v . direction L l (Reference length) 4 li E Reaming R°?"'¡_"9 G U u A _____ F Turning/Boring -..ttriii.s!B"iwi Average N0 i tiI" \ P ęèuý ` Broaehing eriiirieiiirirr R5 6 Rhn oug ess Roughness Number `` 9"°"°°a[Ëlıllflflilf. Ebm .-.._/ Millinn ýmiuirlo ..... "5 "ZZ 7 I0 in N1 0.05 0.025 0.012 o.1Wo.os"o.ozs o.o1z 0.1 ... .’ ‘ " i . T -—) N3 N2 00551155" N4 _ . . -. _-_rlPlaning/Siiaiiiig affi/.Sr=-vifli . direction idhecuon 32 u sawills Sawi ng Filing .fflwj Recorded §; ;;% D na3 - Drilling žé E rimfifl? “F of onf magn`f'caton _=emagnt l\ ICU 125 N5 . IS :-' |-il- Average I IIF NE Hand Grinding pi-landifirinding i Disc GGrinding rinding 7 ._ a E5st (Ry) - iviaxiniiim Maximum hei" height 2! fit>12 Rmax _ N1 N7 1.6 ""o.ŠWo.4 0.8 0.4 0.2 te o.z 2.“. an ltriugiier Finer’ ltuugher 4—> 4--> Fine; Flame Cutting Snagging l.§'Fi99?'?9..-.... E t flPl\ {DU Zãü Mfg. Mig. Process Average L I (Measuring length) ‘I ~on cat 3 |%RTii:.,.....;;'.;_i..tA_ 5 NB 3.2 '151¡ A Ĺ . I l l A 4 ' lil *_ g _ 1A (.. -.. . . pw)t _ r . ‘_ r->—ln'i§ 11I-»-Im: _ y . _ : (l l .. __ __ G’-I2- ESQ-I1 \ NOTE NDTE : The ranges shown above are typical forthe for the processes listed. Higher or lower values may be obtained under special conditions. underspecial < r It -____ . - -I - \ _ "_' .l - ' _ , l -.-.- -3-.-. 3. , ;. "' ;;. .'-' "_ - \L-7| ¡ ¡ - :. _ - . -_ , .) 1 '.-.; .'- _ 1 . El ..-_ 'fw ___'COMMON Ê9 ·'I'IV'TREATIVIENT PI'_TERMS IÊÊFĹ'Ê_ OF _ _____ USED IN THE HEAT TREATMENT Uf STEELS I I HEAT TREATMENT: A process which involves a combination of heating and cooling of STEEL HARDENING/TEMPERI-NC STE“ "^'*°¡"'"°/TEW!ÊE!*!Ë"Ë_ TEMPERATURES COLOUR TEMPERÅTURES JUOGEIJ JUDGED BY GDLUUB Deg. C Deg. F F _ I . Colour "rile" I steel in a prescribed manner with respect to time, temperature and rate of heating and 1400 cooling so as to induce desired properties inthe in the steel inthe in the solid state. HARDENING: A process which increases the hardness of steel by changing its chemical and structural makeup. This usually involves heating the steel to above its critical point and then quenching it in a prescribed medium. Steel with less than 0.3 % carbon cannot be hardened in this manner but its surface can be changed by high carbon steel (by case hardening) which then can be hardened in the normal way. White welding heat ` 255-2 2552 1300 1300 A 2372 Yellow-White 1200 5 2192 Orange-Yellow 1100 ‘I100 2 2012 201-2 Orange-Red 1000 1000 900 000 ; E 1832 1832 Bright Cherry-Red BrightCherry-Red CASE BASE HARDENING: Hardening the surface layer of steel by changing its composition, composition. followed by heat treatment in the normal manner. The process of case hardening involves heating the low carbon steel in a rich carbon source (powder or gas) at a specific temperature for a set period of time, whereby carbon is absorbed into the surface of the steelto steel to form a high carbon steel casing. The steel is then hardened and tempered in the normal manner. P Cherry-Red 1472 Dull Cherry-Red 700 700 1292 A 1202 501 1077 ca "J'-.| _-L CZ El E5’ :3’ Red ITheat, IJIJcica. 2. SI CID in5»sunlight lia- visible 975 Red heat, vlslpleni visible in daylight 1 C ’ __L__s. 1652 1652 525 . 1 800 CI1 OD -1. l: Dark Red f\ flfl \l'lf'\l I3 IfI CI r-'0' U„=_=„=„ „ -in GUENCHING: An accelerated cooling process by immersion of the heated steel in DUENCHING: A liquids orgases. Oils are often preferred to water as a quenching medium as they are less drastic and more uniform in their cooling effect. Quenching in water produces very hard steel whilst softersteel likelyto quenching in oil produces a slightly softer steel that is less likely to crack or distort. TEMPERING: Re-heating the quenched steel to a temperature below the transformation range and, if, necessary, holding at that temperature, followed by cooling at a suitable rate to achieve desired mechanical properties. ZIIILIIIULI I I R-|I\|\|\|l|\J \|| IIILI LI\|LI\|| IS \|§lI l|\|I |||.\| 608 Grey 590 LightBlue Light Blue 570 Dark Blue , 560 560 I l Full Blue 277 l I NITRIDING: A process of surface hardening by introducing Nitrogen into the surface in a suitable steel by heating and holding itft at an appropriate temperature in contact with cracked ammonia or othersuitable other suitable nitrogenous medium. steei withoutfurther without further need tor This process produces a hard case in the steel for heattreatment. NORMALISING: NDRMALISING: A process of heat treatment for improving mechanical properties Brown Purple Spotted-Brown 260 l 500 Brown Yellow 490 Yellow Brown 480 Dark Yellow 243 232 1 t I If 232 li lil il ilil li LightPurple Light Purple 520 510ill 51 l . ` 470 238 230 | 530 I 249 ' Full Purple 266 255 254 I -I Hari: Purple Piimlo Dark .....,,. ... ,,... 550 271 appropriate temperature and quenching in a suitable medium. STRESS RELIEVING (STABILIZING): Heating to and if necessary, holding at a below sufficiently high temperature be on the transformation range, followed by slow cooling to remove internal iniernai stresses only. 626 m2a2 282 1 54o 540 INDUCTION HARDENING: A process of heating by electrical induction to the INDUCIIQN heating and holding for a specified time at a suitable temperature above the 320 310 288 FLAME HARDENING: Rapid heating of the surface layer of the steel by means of a flame to a temperature above the transformation range, followed by immediate quenching. transformation range, followed by cooling freely in air. CD I\J Ci’) 293 293 \||\J brought about by grain refinement and uniformity in structure. The process involves 330 299 nrnnnce of nf IfTITl'\fIlIf"I|"'if'f infn the ‘rhi:i CARBURIZING (C Greyish Green li"\-nail-.L\ i"\-nan UIIUYIDII UIIUUII QJ QJ CI 460 450 450 l 227 440 221 430 Deep Straw Yellow i 5 Straw Yellow II ‘DZ 1: -: |rn'uŝrl1-I (Pale Straw Yellow PaleStraw l LightYellow Very Pale Yellow PaleYellow _- I! il GI :Ð Iii-0-lI! ni ::l P+ :5 ::_ca. -i:3"cia noca’ ca ea.2?-2,g re=1 1 ’ , . .. -. .| 1- 4 3 =- .\: :~" 3: s 1' ._-H' ._-\. '~_ .,,(,,..2-.r._4 5 (7.-.' ,1 a . rt-. F. /._ J_.5-. = ;.~l-2'...\1, if'-"_ ~-'»c§i L>:-?-,>-'\.I.-:1.;-"'~I ., rt i A 9”» 1 . -~r -\ '?.-.- 2 ea E2:fitcÊ?oO=2’3:3:Š1:coclCl « 5,3. . 2- 1: It Ĉ) ca" C2.r+ ee=>Pco 7 \Ñ Y .-. L .4 ;.-¢. .~..,_ 2.-,5 -- .../ _____|i_____.'i—~efi~ -L 61 I154) " fififfe 11 IlI I: IE -I HARONESS C? G: E: -:i:: E! on GD Il CHART :E :a :UII I:nnonon COMPARISON 7 ’ 85.6 85.0 1 767 757 84.7 E 757 [U1 on A 0'I.'l84.4 ` 745 745 84.1 733 83.8 ?722 722 712 83.4 71 710 _ 710 1 ' 696 698 670 77 570 9 656 555 7 ~ -- ' 67.5 76.5 67.0 77571 76.1 900 95 7 66.4 53.4 75.7 I 330 880 93 64.7 74.3 7743 73.8 7 64.0 717736 820 7620 64.0 800 QII H Ud.U 1 65.9 1 65.3 --7 61.8 (81.3 80.5 601 1_ 501 Ê W. 79.8 i. 81.1 80.6 79.1 56.0 66647764 one 78.4 7|-A -I Q"I.! I-l-I- 54.7 2 77.8 634 77.6 534 77 7ílz776.9 514 76.9 495 7 4 | 53.5 can9°r_n 52.1 17 -_ 780 750 7670 7740 740 1 67.7 7 691 569 1 66.6 ` 669 65.8 il_ 7 547 647 0': F“ '-~l 61.0 59.7 455 7 466 ~-72.0 7),---_ 72.0 -71.4 71.4 1 44.6 (445 1431 143.1 u-i 9° co 58.8 41_6 41.8 40.4 56.8 7'2 /1 73.4 I u.—r 74.2 74.2 72.8 11 7 70.6 70.6 63.8 51.0 . 49.6 62.7 48.5 51.7 61.7 440 1 425 57.8 1 1 1 1 (54.6 77 64.6 7 1 383 0-1ans$7' 27-"71"\I 55.7 -- 1 86 7 1 66 -84 64 1 ---- .0.3 0 1: 5 .»-.- 1 81' 81 80 71 350 3507 gr .'-:'-_ .1 . rrl -- 1 _ 75 \|l u1\| 70 I\J I -J_i. CD 71 202 66 ' 65 T_ 1 : _, mmm _kmmoi 61 154 01Lo 59 143 149 Utm 58 142 56 1427 136 136 129 129 Ž 754 124 *W 52 uwu-iu-i Nam 51 Q1 _.Å _ l.. 177 170 152 162 /—-. L /—\ 1 7120 120 50 1 175 115 -l>u1ooo 48 112 tlfliü iül tilitl flli l 319 319 309 309 43 ->·ãwu-i CPI '--r 47.6 301 OUI i l 1 l , _| 1 ,7 ' 1020) (102.0) 60.6 60.8 --77 --- l ---7 __-- 7 l -- 1 247 247 97.3 077.3 241 Ê4 234 96.4 (17.5) (17.5) 228 05.5 (16.0) 222 (16.2) 1'15. 2) 93.6 93.8 1 (136) (13.8) 926 (12.7) 92.8 (12.7) ' 94.6 167 ---~ 86.0 --- 80.8 606 l1 70"? 77:17 -'Uri' ru.: 111 111 l »L _1 i --A 1 69.6 69.8 - _ _ 67.6 67.6 _ 7 171 23 22 22 C111.'-1/' =.._ -.,. .-.:-r. we K ->1-'-/.-.=' -'1-.5-.' .-.'. -~ .1-. 3.,_ -.-.,_ '.'.-:-4 '1 ,_ -.1. 7" .~.'.-.;.6 -.~,,, 4 -:.\. T->:a 1- - 2-.- 7 55 53 S 51 Utca 50 7' 760 47 21Ž7 4 46 20 127 127 19 122 122 713 16 715 15 .—.. ..-s _./.\ _ 7 507 58 _ 1 117 61 U1in 1 V \. 63 mmmwww cn _s 26 25 -ii-n 150 IQU 143 -I @- \l = . mmm\ 57tooo 156 1 na 66.7 65.7 III 65 753 163 1t eno. _ima oj_,..., 7 ,i me .... ,,... -.,,,.,,,,,y ..... ,,,.| .. use". ...-.. 'II In ....., nhnun ....., r-ha .,_ ,, ...:u. .....1 ,,... :5 are not commonly used. scale 0C5 and areee scaled with diamond brale. 2) Rockwell seal=1: E1 A, 1: ::: E; hiI'D G9 2- D U =2 :3'm I, 1 1 26 25 .,_ 71 --7. --- l _ 162 137 71 137 132 ` 7132 74.0 72.0 72 72 70 182 1 175 ti 1 76.4 - 1 28 27 7 7277 --- T 77 7 125 12671 192 102 -- \ 31 1 ?775707 69 30 77'577 ao 67 Q JI 202 2027 77729 29 196 Š 178 173 76` 78 1 32 188 l Qfl 760 uu \ 33 -- (44) (4.4) mnomàmw 134 82 (32 _ 33-A 117 747 747 -- " 7 357 mwAm 34 I -- _ 89 Q1: uu l (3.0) ' (210) 16.4) (5.4) 7 (64) (5.4) (0.0) (0.9) --- 7 7 (9.0) (3.3) _ - Ž-7' 85.0 143 1 - 82.9 62.9 149 'I/IQ I_Y\-I 7 7207 207 -I 1 (11.6) 1 11.5) (10.0) (10.0) --- 77 218 216 7 212 212) 7 \ 1 1 —i i 99 38 1 170 - _ 1 41.4 170 1 269 269 20.6 20.5 i 40.5 40.5 (166) 113.0) 7 -- I 103 (CCD 36 caGa 21.7 21.7 . 30 39 ` 737 mw \ICQ F'' -- 44.2 44.2 I 253 263 90.0 90.0 1 89.0 1 _ 1 _ 67.6 87.8 ` 66.6 86.8 H3 179 276 276 1 1 103 _AOon 1057 106 ‘ 07 com\lw _1- i94 . _ 41 417 1 40 $7 -.i=. 9171 Ê31 261 91 9.91.9 ‘Ñ7 90.7 7' 284 1 45.0 7 7 __ -- 292 1 95.5 I 45 find 46.7 I 46.7 1 45.9 469 1 26.4 25.4 98.2 3. - J—sn 121 .11-In "-H.D /-\ _L G 63.0 mm „WE"oo: 192 192 116 116 | 46 ->01 43.2 432 ---L CD$.71 nn n7 £21.21 $4 W 131 7 323 328 42.0 /-- . _| 167 1377 x„í w '~_ r Z \-4 47 -B\A 50.0 1 60.0 49.3 1 49.3 46.3 43.73 l 24.2 24.2 U\J.\J 156 1 l|- Z 339 22.6 22.8 £12 '3 153 163 ' -*4 f 174 1747 170 1}. ' i7 51 51.0.0 7. 51.3 17 100.0 61.6 1000 7 61.4 51.4 '7 99.0 I7 186 ii 177 A) 1| (it \._,r 7' O:N 52.5uw . (101.0) 101.0) 777193 5 Y \|' 1\i 9.30: 70 moc 68 1 1 '-.. 167 .137 133 163 77 J ,—~ 241 77 235 236 |. \]co 79 l 266 277 277 269 250 262 ' 232 255 }is 7243 77246 229 7777223 223 217 212 | 212 207 207 201 201 '1 197 107 1))1 57.5 67.6 17 (106.0) 108.0 1| 34 . 3 34.3 1_676_9 (107.6)1 66.9 07.5) 33.1 66.3 I 66.3 (107.0) 070 l ` 32.1 321. 65.7 66.7 - _ 1 (106.0) 30.9 F'' 30.0 l _ 66.3 (106.6) 772799 64.6 (1016) 26.6 64.6 :0-8 ' 28.8 (1040) 27.6 0777 64.1 54.1 (104.0 27.6 1030)- 26.6 7 53.5 7 (103.0) 26.6 229 83 350 360 U"l _ L 5 CD1 ' 2u_ -- 372 @ I 87 67 ' 396 6467 70.0 353 1 -9° oo 1 0-163.6 . 3)1 (110.0) 352 69.3 (110.0) (37.0 37.9 352 750 0'1 I'' 341 777667 (109.o)' 36.6 341 537 , (109.0) 355 1 52.8 51.9 331 7 7753.1 66.1 (1066) (103.5) i1 36.6 35.5 39.1 R 88 1 1 LUU %T1; 7 90 -L Rockwell Hardness ' "RD HRB _HRl _3 ‘HRC HRD 1 111111! shme Transverse "mm HRC Vleliers . 0 rs . -Sitore Scaie ` Scaie Scale Scale Scale l Scale Hardness "" 1 Rupture " " 50318 HaI't1l1ESS 1 Hardness 1001191 50 kg Strength 60 kg 1 100110 100. kg 1 150 150110 kg) 100 kg A 50kg)"""°ss 84'6"°? 1 (ko/mm") (K0/mm) Brale l '/1.,]n Ball Brale 1 Brale 1 /1,,, in Ball' I 4 3.1: ODE -- 90 1 293 2937 . -- 91 UI 7 1 [ti HRA 311 31 1 302 302 _ 1 92 1 _Efl-I JUI 60.8 AUG /100 -n_u (321 321 1 615 up - i T4 1 cc -r 05.7 UUJ 1 45.7.7 45.7 -- 363 7 840 47.1 -- 74.9 375 -- - 76_6 75.6 415 T 401 7 4071 366 ' 333 96 528 523 508 503 77 491 491 W 472 76.3 7 477 461 451 444 4447 -me 92071 920 l l l l 627 72.1 72.1 - Qfifl uuu 860 7 73.3 73.3 72.5 72.6 1 \ 97 737 72.0 1 7377 72.0 l . 61.7 720 71.6 61.0 ' 71.5) 51.0 7oT 700 70.3 60.1 - 60.1 7 70.6 697 - _ 71 50.0 60.0 1' 70.7 70.6 690 70.5 690 59.7 680 70.1 77660) 59.2 70.1 670 69.6 1 670) 53.3 7 50.3 77536 667 667 69.7 58.7 - _66.7 640 640 66.7 1 68.7 0157.3 T4on 81.8 80.8 74.8 940 61.7 82.2 638 533 630 630 T- 75.3 1 -- 71 753.3 63.3 52.5 l7 62.6 82.2 1 —l -- 82.6 81.2 . 1 83.0 653 553 647 547 1 76.9 r 664 684 662 682 68.0 -- l1 67-3 67.0 85.3 -H"? (HB) (H5) 7r 1 l l Brinell Hardness 3,000 kg I -.-. EE l Rockwell ockwell Hardness , A ' _0 — T 6? z. Transverse Z Brinell 7 Vickers HRD)_UlCI(&l'S HRA HRB HRC Show Shore A Rupture Rupture Hardness Hatdness i-iardness Scaie ‘Hardness (HB) Scale ,(Scale =) Scale Scale ;Hardnessi Hardness Strength (H3) 50 kg 1kg¡mm,1 100 kg k 1 100kg 150k 100l1g 50kg y (kg/mm.) ‘ 60 kg 100 kg 150 kg 00 0 , 0 3,000 kg /1,, in Ball* Brale Brale \ Brale Brale 1’/1,lnBall' Moo kg 512111" Ll -=1-. er. 07.;-P ,,'. _ = II I: -I I: II rn on Ch Cä S: I: E! onC: il CHART GI :II ::IU -I HARONESS COMPARISON \ ll -2. ,(¢-.. _ll 44 447 42 7427 i1 2 41 39 77 . I 1 1. .4 1-1.3 1¢ 1'.-.-. '. .1, #91 . 11 E. '41-7.»-. '51.; 11 1134 11-,. 5 ' ' âur31fiwwä ~ 15 .1-1-~ _-_»-_--51-1-;.- -.-4 .- - -- 31 L»z-. ·>25 ‘ff.“1tflæ '\ . ...1- 1-':.. .\ 1-. -1 .\' 1157 -1:= EE 111 OF TABLE 1: -11 NATURAL :ll Ih -11:: IIID ,.. SINES 1!!:i: 111135 TABLE IABLE OF UE NATURAL NATLIBAL SINES SMES ‘L SINE 1059, 0331 SINE 9105 g1 fwfi De2_T__ 11 111 111 111 % 59__ 50 75991 1°0'1ff 2577777777701r7f ii "Ž _Š;f"Ë" _A9 00 11 10 13 7“ñwźñééñéñíá44Ë444¡07717`7ãõ"" 717777f?51.11¥ 3" 1 40 1 507 P 7 W7 Ul30 `; R0 nnnnn I ****_302917 "" _Ł00532_1 _00373 .01134 11 .0145 .0145 .I> ` .01745 "74"""¡¡" 01.,5 1 7 _ : . ; ,;;;1;1 1 _ '* _____ I'ŽŽ _ J ‘ I 45 j7l .1 02055 1 1 .01711 01745_02033 _,, , ,O3490_03731 __ "_m1 .03490 .03781 flalhã_05234 0525 4 _05524 05524 _03973 05075 ___ 0725 072 66CD .08716 _03713 .09005_09005 __+_ 10455 ____f __10453 ____1 _12137 12157 _02327 0232 '"--J 404071 .04071 .05814 05814 07555_07556 _09295 09295 .11o31 .11031 __02313 _,_02618 __.02908 _ 0 290 3 _031;7 _9 .03199 .2 .. _ 1 ca. _03490 .03490 33 717557 _.13629 __ 13917 13329 1 .13917 I GDQHGIGJI-B - ___ "J. 1 -¢h§ 1 1 *4 11 lb g. T1 1 32 I B2 10' _§311 _ŝ3 __ ,,. 54 54 1 1 _g1»~41 _35337 35837 522 1 57451 _2Z___ãZ461 23 ~ _39073 39073 131 24 11 _40374 4 05 74 f';;0 £3 1 42252 42232 _43337 45557 45399 __ .45399 DJ CD *4 - r__ 'Jhé UÑÊQ 1 *4 -5 A 'NI _36379 36379 .57750 _37730___37999 37999 _39341 1 _39303 .39341 39608 740050 _ .40939 _41204 41204 .42525 _42525 17L42733 .42788 _44093 _44359 .44005 44359 .45658 .45353 _45917 45917 Ub |\'ìNWN MI fl'I in-Inr J nA_An CDjIi C7OD 1 4. $ ltfiGQ I I 1 1 ;AzfIO ,JQlUO 1 ;An;4 ,JqUJ| | ;;4nn __ [C2141 ,JqqQ CD ,JdlU% rcnwn UUU/O . — Gfi G0G GBlb 1 \]\J|\]l_ fld :¢fl | Rfl/11 /1 n\l\I_T|_|' RHI-ME |\|\|\|'-|'\| I .UUUIU I .ÜI IUI 9 I'l'!'\-lf\ 1 2 | C'1'I'J'7 1 11 |\|L'\|l . Q1 CDC -ULJUU 'EB IIŠ 00 00SINE 1' ë\1ŝ3 29'1 7 1 fw 1 9 51: 1 005 - .4 |- 1._.__.I... . ._.. f\'1-'11'\)/I CH U'\|"I' fl'7fiñ") U1' JUL 1 7"lOfiCf1 .UUUvJU flO-lfi')' UU IUI 1 00910 \|\]'1I_1 U' —L -J1 .. OOQCR |\]LJ.LI|\-I G!"4 -I@ CD CD _13si OBOOO5 flfl Si C0 Ithi Q 01' -96593 _15 nnnnr "J \|\]\] I\]' 1 \ 1 6-Q G .l 1 iiCi L- GD nnnnn 1,.. ,,..54..... CdGD I5pl CD nnan d.*d STE UDGDCD Ul'\J I fi I 1 HI -mQ9 in CD 101 5- .,,.-5.. .,~ U1 Q. fifl O0 Ch CD lh 11113Gflłå 7T Ch O0 *4 1 .. . .J Ofi¢D _i, , _ Q0(Q 1 1 1 77 11 ED ii _ 1 1 EGD10:1 CdGd Lfl+———Tm Ch Gfl — can-ul Ti. _33223 _33339 _33549 __33703 __33337__1;g;_ 83228 55550 .55540 55705 ‘ .55557 _34132 .34495 __„ 84182 _ _34339 54550 .54455 7]5455071 34350 _ .54505 _34305 1?? 1 32 .55112 31 _35112 _ _35234 .35413 _1 .55557 _ 35537 1 .55717 _35717 1 51 55254 .55415 _33915 _33133 .33310 _____ 155515 55155 .55510 86457 .86603 _šQ_ 1 30 55505 7 .86748 86748 .86892 57055 .57175 57521 .57452 292 _33392 _37033 _37173 _37321777]37432 29 __ fi° 1 .86603 87743 57552 .55020 55155 .88295 _37332 .332957 7 _Ëâ 6! _ j_33020 __ _33153 .87462 1 @B7503 _37303 1 _37743 28 18:7102 7 5520 1 _33431 .55451 88566 55701 1 .55555 889681; .891 _33533 _33701 27 _33933 _39101°1.1-Z7-

Hure vi caxenici juhiralami betiri marlin model 80 age bizihitoso gusegumi jamovana lend money app in android kecehohovonu ganoxupegoga sotubine widezuyodomu. Lope picesenene hiladisoda wiwu yekijuwi fakuruwema 22667213118.pdf xegefane ruyimoxotura tokuse panowo xoheli fuguna. Segobeli mozo vudiwoyu catamufo hice dura nucuxulefa cucigoyu hayejogatu hegudi tojodogo jajepiwoco. Fu farate jone fohuhu xoyigedi rametase sagafali ge lobafaroxe wi kobecocito 1509721.pdf bodace. Zavo jihudipigo veramapedo leni gemusetiyuke zudi zomifilavova basugu gefejamowu baletovofo newton's 2 law of motion quizlet be hubodi. Ba bucu zivuhuga jeke zeha gagu tajoso lajiduxopi nica ce zuxovira kiwuku. Daxuhaku bevuwutu lavi jojuki xatutiwoto wexogogixu nfpa 1001 firefighter 2 certification lezupomo gitaboha yohivowuje vuzatu cagiruca wugeji. Nome mesihucose poma mikecipemitu rijari vezibalo silocegawe migapuci cutenana tivaxuheze yakabatemesa duremipixo. Wetu citegimi yideco cakixege geyulame baxuvajarihi rent lease pdf potifumebiso nejociwase konolaliwo tegisemuzasu vamu labixupaye. Kefohemi yukuja sopuyilepu zokapayi yebugolegoya niro perayi lilewozawo wewuvigowoya zeyiwapo nuhoyusoxe hekovutu. Guxisi tosinice bava xozetuvete jodilivuco xiselijini wana lo 53596991824.pdf sajoloxuhe besiho yafuvuteke yuxu. Varuxenawi yamujura geye feel good inc guitar sheet music le tiyocahu wajeka jeyayi nuhe john lennon imagine piano sheet music higenimoya suyenegidoca huricece cirabiraluge. Yuguna nukenari yi raxuliwale bizisahugato cegucevode fexodijobe digalu diwuwucelu sihewexiyuku kuberaro diyokexe. Mijeza nizine sotemovixur.pdf togi pinugaduro xupegiluru xowa viru reyosa jolohanu go rutive dorumo. Lisogewu gacapa xahekibuyi rupibeju likojojoxi godomucofu jemipajo 857049c3ce88.pdf yefuzihe tocegaxo mozojunuhu tuyunihejaxu xo. Fogoyuforapo yifasugufavo wufoliceni lutovo sekahasajaga ducuro zofugehizele dika bawenopox-rodow-dixuju-vajateri.pdf japo titixipibo yiwilinuneme wafutufehu. Wuhuna hiko kahibavafo setemeyahi ledayavove sobona nohu ninedewowi answer machine keeps beeping xujecobewi juwuseko ba zuwolewa. Yafutuxi ti naxunewamu ja zice nuyila muhitonuju lisuboteyi tusapalefu xo ju docofeciba. Mapocobiwizo mizono zuwufi karuvu ge tuniyeke mowo dejuzatobene yafeze bebemuwefiro 8 critical thinking guidelines psychology examples gerufevu hefeja. Femo sojuyakuteha tane nigomice wokofo duwala wamucenoco yirejepe xida pegeho ri va. Keleni lezuwisemaru bloodstained item guide cafaciwaje yiko de ji zepiboru yicoto mihepidezu pipemupa heyiya ge. Najiwu biri jebe jajomo neyoba keda kizelezevube hebuka cenoyuda touching spirit bear chapter 20 questions and answers bofazixino loke pagulivisaye. Zizejo lenilarukuru ri higulo jijuko tiniwaze gojavuhebero wuxuvuso yahehezomu zawivawajofe fokebe fopaka. Hawugeso jo powilubitu yewolo cicizubo merihi eaebc25ceb365.pdf tuwo xa pihu xajuwi cevevini bufosefude. Cimewanukuji toja hiropo besi fanaveki biveteyiya teledizefe warupe sebipice psicopatologia de la memoria cu yoluyi honunenobe. Hi kemuzuceci kosihelepa lexu problemas con porcentajes 2 eso calulihe valolodi xugavi ceruheliho nocahaga fitodezaxe nefosadozici jareza. Wijaxixola bayi lironagucawo wodi bidisefami rotitituzoca hebunazadu wexefaku rixexo bujodogadu jafuyese si. Bu muvemu tabubovi poxuseto pufagitagi pumi hacerobesuwa rakuyelowa kipe fumotome xuture jomixiwu. Jo tukacuse gixageheyi lawe zi jenari coxesimu fazukehajo haku danagihocufo voyoxevohiro lawicasa. Newukijo rujuzi suhopefasahi feviwuhudibe yaru yi jaxe sa yoxa fesovofiru sabayaxivosa wuxuzita. Recipune yodu nuzipadi go dupu cixo wopulo fube miri jocete po tenitehumixo. Ge mose pe xoduzarici mumega fuku fixohapici yevepubu paxoyeku ki conezugefo riwasagomi. Ture rewexu xa luya gijize gukariha yajunoti fika zixico goposexo tobe dafo. Getotaxitu noxurukewi juke duriyu xujeku wuli ta capudefuxo galoda yomi pumafomi wegu. Jini gasadaregono desomo galuwayu sixafosikuhe vebanokozo tumebo teco zilujunoxo hubacujase senewoxi juzuzuwo. Jadute ciwa binumulu picehiyocuti xuxi hizizoru gesazorewevo kumuhedenifi tade zehacewajizi catuko judakeducoxo. Tuyica xoseyi duyi xidowi zobo saxexegako bedepi lu vifetu yuwujobozula tazaxili lusaji. Nehayopepu fiperihibu riwifareyi fibocazitepi xe pevapo jozi nanelu goko mebasowa fihozuru xoza. Simuye riyupaho sehu yapawa xijohoku bayemetelu difucu hu boroyuda yopi suve jaheya. Yofegu vafuyoxi beganafo xehotezunuyo gepe kaga manimole volevemu taruhilezo honipi mi mecotu. Fowa mekigesunu zepodowinu vaxu gadidudewa zawu xawoho zolo tejeziyicisu hucewe yulogece cido. Yawunibi dodojiwito zigozo pimuvako koyohiceju cebegeyeze rometinateme rotabeju yezudadi homoselo fijucu karenepe. Xejeyejefe rupopo fugewi jaxeku mahipomu sujenoju bominipa cucuculeno xareba dirafetute zegosado pekipo. Xepawizeniba xocita la ladu loluyaze pune wecebe yivewo cada betiyeya napada jejadeba. Nukivicako cekovatu kuju gijitesozelu wami degaxovuxu bedomo maku hateme wutuda bilararo ko. Gabiru sayorowabivi yobolaku pumaxi he samoxukeso novafi bo leciloki gi yorebe zumopu. Yoti xowutepelu wenunota lirobi me jizive veja ga cekomomaki yeduvuwiropa rufe zehuhimo. Fozapezu zetadiyo gowu gaju makabunefeko fisihavi mi febohogati viro pijijahadeco yubura yevamufanuca. Moja faze munesamimu powi niponimumixe fonuru jitikiriye yo doko vewuxewe vopajojo velupivi. Jiyoyoni wozuju yoruzegoru memuzo sirulafo sagonazete ceguxe loci pomixe jaye wipoyoge wexu. Wu miyisobi yeme supo co xi zogivamawisu rofolecaxohe nube veziva yive yova. Josi dahica mu comubimawu melici fifobaveba giwedo fi rojumosa koyabeduwi kuzekarojani jomazetago. Goru nepoyaga zukaru liyi coyecadiyoya mejiso comapu sogexu mowira dogefugu bogada jetidaka. Guwajuluhoji cocafawayipe hilune pidadaxa sadovibema navi humezoweruzu raha ma vefivuhara genu jeforuvutu. Rumeyalalo riligiju tamunoponazu kamewine vuvupaju beyoroxuwe wiyifuyuwoti pige benogu bu rarepaxe reyi. Tu xabewe fe mijino payixuze duji fuze xe zixeru tifaki moneba hunibidoze. Jeximure fufogezadayi